

Perceptive Accounts Payable Invoice eForm

Advanced Design and Setup Guide

Version: 12.1.x

ImageNow Version: 6.7.x or higher

Written by: Product Documentation, R&D
Date: August 2016

perceptivesoftware
from Lexmark

© 2014 Perceptive Software. All rights reserved

Perceptive Software is a trademark of Lexmark International Technology S.A., registered in the U.S. and other countries. All other brands and product names mentioned in this document are trademarks or registered trademarks of their respective owners. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or any other media embodiments now known or hereafter to become known without the prior written permission of Lexmark.

Table of Contents

| | |
|--|-----------|
| Configuration overview | 7 |
| AP Invoice processing compatibility matrix | 7 |
| Configure a workflow for AP Invoice eForm | 8 |
| Example: A configured AP workflow process..... | 8 |
| Create or configure a workflow process for AP | 9 |
| Configure routing rules | 9 |
| <i>Create Invoice Entry Validation routing rules</i> | <i>9</i> |
| <i>Create a GL Coding Validation routing rule</i> | <i>12</i> |
| Add the eForm and iScripts to queues | 13 |
| Configure validation within the eForm | 13 |
| Enable validation for specific roles and queues | 14 |
| Configure the duplicate invoice check | 14 |
| <i>Duplicate invoice check</i> | <i>15</i> |
| <i>Advanced duplicate invoice check.....</i> | <i>15</i> |
| Configure header-level and line-level required fields | 16 |
| Configure GL code validation | 17 |
| <i>Configure the GL Codes source values.....</i> | <i>17</i> |
| <i>Configure the GL User and GL Code virtual tables with constraints</i> | <i>18</i> |
| <i>Enable the GL code validation.....</i> | <i>18</i> |
| Configure GL account validation | 19 |
| Configure the Invoice Total field validation..... | 19 |
| <i>Configure amount validation and distribution in PO invoices</i> | <i>19</i> |
| <i>Configure Invoice Total validation in non-PO invoices or credit memos</i> | <i>21</i> |
| PO/invoice currency validation | 22 |
| VAT validation | 22 |
| Intelligent Capture Connector value-mapping validation..... | 22 |
| <i>Lookup validation.....</i> | <i>22</i> |
| <i>Date mask.....</i> | <i>23</i> |
| <i>PO line items.....</i> | <i>23</i> |
| <i>Replace vendor number.....</i> | <i>23</i> |
| <i>Location code.....</i> | <i>23</i> |
| <i>Configure separator for multiple PO</i> | <i>24</i> |
| Configure caching..... | 24 |

| | |
|--|-----------|
| Configure value added tax within the eForm | 24 |
| Create and enable the VAT codes | 24 |
| <i>Create and update the virtual tables</i> | <i>25</i> |
| <i>Enable the columns</i> | <i>25</i> |
| <i>Enable VAT at the line level.....</i> | <i>25</i> |
| Enable the VAT amount summary | 26 |
| Enable VAT amount validation | 26 |
| <i>Update the Currency virtual table</i> | <i>26</i> |
| <i>Enable the columns</i> | <i>26</i> |
| <i>Enable VAT summation and validation.....</i> | <i>26</i> |
| <i>Configure server-side VAT validation</i> | <i>27</i> |
| Associate the vendor VAT registration numbers | 27 |
| <i>Verify or create the VAT Registration Number (VAT ID) Vendor and Vendor virtual tables</i> | <i>27</i> |
| <i>Enable the Vendor VAT ID field.....</i> | <i>27</i> |
| Associate the sold-to VAT Registration Numbers | 28 |
| <i>Verify or create the VAT Registration Number (VAT ID) Business Unit and Vendor virtual tables</i> | <i>28</i> |
| <i>Enable VAT at the header level.....</i> | <i>28</i> |
| Enable the VAT Compliance check box | 28 |
| Enable the Automatic Tax Calculation check box..... | 28 |
| Associate AP Invoice eForm with other ERP application..... | 29 |
| Configure AP_Config.xml file..... | 29 |
| Configure real-time posting in SAP | 29 |
| Configure real-time lookups from SAP | 30 |
| Configure eForm for data massaging to SAP | 31 |
| Customize document key mapping in ImageNow | 31 |
| Configure goods receipts within the eForm for SAP | 32 |
| Create and enable the goods receipt document | 32 |
| <i>Update the virtual table</i> | <i>32</i> |
| <i>Update AP_VirtualTable_Updater.xml.....</i> | <i>32</i> |
| <i>Configure AP_Skin.xml.....</i> | <i>33</i> |
| Configure GL distribution on PO invoices | 33 |
| Configure GL distribution of additional costs not associated to header amount | 33 |
| Configure add on cost (AOC) on PO invoices | 34 |
| Create and enable the AOC codes | 34 |
| <i>Create the AOC virtual tables</i> | <i>34</i> |

| | |
|--|-----------|
| <i>Update AP_VirtualTable_Updater.xml</i> | 35 |
| <i>Enable GL distribution with AOC codes in AP_Skin.xml</i> | 35 |
| Enable multi-line GL distribution exports for Lawson | 36 |
| <i>Enable PO GL distributions in AP_Config.xml</i> | 36 |
| <i>Configure the miscellaneous line export in AP_Export.xml</i> | 36 |
| Display or hide Purchase Order Lines in Invoice Details section | 37 |
| Additional fields in Purchase Order Lines | 37 |
| Configure AP Invoice eForm for a global environment | 37 |
| Configure language, date, and currency settings..... | 37 |
| Custom configuration..... | 39 |
| Supported languages, countries and currencies | 40 |
| Additional supported currencies | 41 |
| Configuration considerations | 41 |
| <i>Windows regional settings</i> | 41 |
| <i>Keyboard configuration</i> | 41 |
| <i>Language Bar</i> | 41 |
| Appendix A: Add a custom currency example | 43 |
| Appendix B: User interface labels, tooltips, and messages..... | 44 |
| User interface labels..... | 44 |
| Tooltips | 55 |
| Error and confirmation messages | 55 |
| Appendix C: Document types and custom properties | 59 |
| Invoice | 59 |
| Credit Memo | 60 |
| Appendix D: AP Invoice eForm file directories..... | 61 |
| \\inserver6\etc\ap | 61 |
| \\inserver6\temp\ap..... | 61 |
| \\inserver6\script | 62 |
| \\inserver6\form\[<i>build folder</i>]..... | 64 |
| \\inserver6\form\data_definition | 65 |
| \\inserver6\log | 65 |
| Appendix E: Custom logic | 66 |
| Global variables..... | 66 |
| Custom functions..... | 67 |
| Add custom business logic to the form..... | 67 |

JavaScript event handlers 67

Call a server-side iScript..... 68

Enhance the validation iScript 69

Enhance the export iScript 70

Field level sample 70

Global level sample..... 70

Appendix F: Reserved characters in XML and forms 71

Appendix G: ERP specific values associated to financial terms 72

Configuration overview

Installing and configuring Accounts Payable (AP) Invoice eForm consists of three main processes. This guide reviews the final configuration process.

The process you have already completed: First, you installed the eForm on ImageNow Server, with steps detailed in the *Perceptive AP Invoice eForm Installation and Setup Guide*. Then, you imported the data required for processing invoices from your enterprise resource planning (ERP) application, such as Lawson. With this data, you created virtual tables, as described in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*.

Finally, you complete the AP Invoice eForm preparation by configuring the solution with the specific features that your back office requires. This guide covers the steps you need to complete these configuration tasks.

- **Configure a workflow**
- **Configure validation within the eForm**
- **Configure value added tax within the eForm**
- **Configure goods receipts within the eForm for SAP**
- **Configure add on cost (AOC) within the eForm**
- **Configure AP Invoice eForm for a global environment**

For information on custom scripting with the eForm, which is an optional setup process, refer to **Appendix E: Custom logic**.

AP Invoice processing compatibility matrix

The following table maps the compatible versions of ImageNow Server and Perceptive Accounts Payable (AP) Invoice eForm.

To determine compatibility with versions of AP Invoice eForm prior to 10.0.0.28, contact your Perceptive Software representative.

| ImageNow Server | Perceptive AP Invoice eForm |
|--------------------|-----------------------------|
| 6.5.1.149 to 6.6.x | 10.0.0.28 to 12.1.x * |
| 6.7.x | 10.1.0.307 to 12.1.x |
| 6.8.x | 10.4.0.234 to 12.1.x |

Note Perceptive AP Invoice eForm 12.1.x, when used with Perceptive Connector for SAP Financials, is compatible with ImageNow 6.7.x or higher.

Configure a workflow for AP Invoice eForm


To configure a new or existing workflow with AP Invoice eForm, complete the following tasks.

- **Create or configure a workflow process for AP**
- **Configure routing rules**
- **Add the eForm and iScripts to queues**

While this section provides detailed configuration steps, the workflow process, queues, and routing rules are primarily an example. You may tailor the workflow and its components to meet your back office requirements. For more information on completing other workflow tasks, such as designating workflow queue leads or drawing containers, refer to the *ImageNow Workflow Designer Help* available at www.perceptivesoftware.com, in the Customer Portal.

Example: A configured AP workflow process

Before you start configuring your AP workflow process, here is an example of a completed AP workflow process.



Create or configure a workflow process for AP

You can use any names for the queues in this workflow process. The names we provide here for examples correspond to the default mappings in AP_Skin.xml. If you use alternate naming, update the `<roles>` element in the AP_Skin.xml file with those queue names.

1. Create the following work queues in your process:
 - APO Invoice Entry
 - APO NonPO Invoice GL
 - APO PO Invoice Matching
 - APO Invoice Upload
 - APO Error
 - APO NonPO Invoice Approval
2. Create the following system queues in your process:
 - APO Validate/Route Invoice
 - APO NonPO Invoice Validation

Configure routing rules

You must configure routing rules to use with the form in your workflow process. The AP Invoice eForm installer created the custom properties used in routing rule setup.

The procedures in this section are not exhaustive and do not outline every method you can use to set up the routing rules specific to your particular AP Invoice Form implementation.

Create Invoice Entry Validation routing rules

To create Invoice Entry Validation routing rules in your invoice workflow process, complete the following steps.

1. From the **Workflow Designer** task pane, click **Actions**.
2. In the task pane, click **Manage Actions**.
3. In the **Action Settings** dialog box, on the **Rules** tab, click **New**.
4. In the **Rules Editor** dialog box, complete the following substeps.
 1. In the **Rule name** box, type **Invoice Validation**.
 2. In the **Rule type** list, click **Routing rule**.
 3. Complete the following procedures, detailed in the following sections.
 - **Create a rule to route back for header error conditions**
 - **Create a routing rule for non-PO invoices**
 - **Create a routing rule for PO-based invoices within tolerance**
 - **Create a routing rule for PO-based invoices outside of tolerance**

Create a rule to route back for header error conditions

In the event of an error header message, you can route documents back to the APO Invoice Entry queue. For more information on validation and some possible error messages, refer to [Configure validation within the eForm](#). Complete the following steps.

1. In the **Rules Editor** dialog box, under **Statements**, click **New**.
2. In the **Statement Editor** dialog box, complete the following substeps:
 1. In the **Statement name** box, type **Error Condition – Route Back**.
 2. Under **Conditions**, click the **Add** icon.
 3. In the **Add Condition** dialog box, complete the following substeps:
 1. In the **Constraint by** list, select **Custom property**.
 2. In the **Type** list, select **Normal**.
 3. In the **Field** list, select **AP Header Valid**.
 4. In the **Operator** list, select **starts with**.
 5. In the **Value** box, type **ERR**.
 6. Click **OK** to close the **Add Condition** dialog box.
 4. Under **Actions**, click **Add** and select **Route to**.
 5. In the **Queues** dialog box, complete the following substeps:
 1. In the **Business Process** list, select your workflow process.
 2. Under **Available queues**, select **APO Invoice Entry** or the name of the queue in your process where invoice header data is entered and then click **Add**.
 3. Click **OK** until you return to the **Statement Editor** dialog box.

Create a routing rule for non-PO invoices

To route non-PO invoices to a specific queue, such as the APO Non-PO Invoice GL queue, create a routing rule. Complete the following steps.

Note This statement is necessary only if you are processing both PO-based and non-PO invoices with the form.

1. In the **Rules Editor** dialog box, under **Statements**, click **New**.
2. In the **Statement Editor** dialog box, complete the following substeps:
 1. In the **Statement name** box, type **Non-PO Invoice**.
 2. Under **Conditions**, click the **Add** icon.
 3. In the **Add Condition** dialog box, complete the following substeps:
 1. In the **Constraint by** list, select **Document key**.
 2. In the **Type** list, select **Normal**.
 3. In the **Field** list, select **Field5** or the field in your indexing structure where the PO number is stored.
 4. In the **Operator** list, select **is equal to**.

5. In the **Value** box, select **Default**.
6. Click **OK** to close the **Add Condition** dialog box.
4. Under **Actions**, click **Add** and select **Route to**.
5. In the **Queues** dialog box, complete the following substeps:
 1. In the **Business Process** list, select your workflow process.
 2. Under **Available** queues, select **APO Non-PO Invoice GL** or the name of the queue in your process where general ledger (GL) coding is entered, and then click **Add**.
 3. Click **OK** until you return to the **Statement Editor** dialog box.

Create a routing rule for PO-based invoices within tolerance

To route PO-based invoices within tolerance to a specific queue, such as the APO Invoice Upload queue, complete the following steps.

1. In the **Rules Editor** dialog box, under **Statements**, click **New**.
2. In the **Statement Editor** dialog box, complete the following substeps:
 1. In the **Statement name** box, type **PO-Based Invoice – Within Tolerance**.
 2. Under **Conditions**, click the **Add** icon.
 3. In the **Add Condition** dialog box, complete the following substeps:
 1. In the **Constraint by** list, select **custom property**.
 2. In the **Type** list, select **Normal**.
 3. In the **Field** list, select **PO Variance Factor**.
 4. In the **Operator** list, select **is equal to**.
 5. In the **Value** box, type 0.
 6. Click **OK** to close the **Add Condition** dialog box.
 4. Under **Actions**, click **Add** and select **Route to**.
 5. In the **Queues** dialog box, complete the following substeps:
 1. In the **Business Process** list, select your workflow process.
 2. Under **Available queues**, select **APO Invoice Upload** or the name of the queue in your process for invoice upload and then click **Add**.
 3. Click **OK** until you return to the **Statement Editor** dialog box.

Create a routing rule for PO-based invoices outside of tolerance

To route PO-based invoices outside of tolerance to a specific queue, such as the APO PO Invoice Matching queue, complete the following steps.

Note This statement is necessary only if you are processing PO invoices with the form.

1. In the **Rules Editor** dialog box, under **Statements**, click **New**.
2. In the **Statement Editor** dialog box, complete the following substeps:
 1. In the **Statement name** box, type **PO-Based Invoice – Outside of Tolerance**.
 2. Under **Conditions**, click the **Add** icon.

3. In the **Add Condition** dialog box, complete the following substeps:
 1. In the **Constraint by** list, select **custom property**.
 2. In the **Type** list, select **Normal**.
 3. In the **Field** list, select **PO Variance Factor**.
 4. In the **Operator** list, select **is not equal to**.
 5. In the **Value** box, type 0.
 6. Click **OK**.
4. Under **Actions**, click **Add** and select **Route to**.
5. In the **Queues** dialog box, complete the following actions:
 1. In the **Business Process** list, select your workflow process.
 2. Under **Available queues**, select **APO PO Invoice Matching** or the name of the queue in your process for PO invoice matching and then click **Add**.
 3. Click **OK** until you return to the **Workflow Designer** task pane.

Create a GL Coding Validation routing rule

Complete the following actions to create a GL Coding Validation routing rule.

1. From the **Workflow Designer** task pane, click **Actions**.
2. In the task pane, click **Manage Actions**.
3. In the **Action Settings** dialog box, on the **Rules** tab, click **New**.
4. In the **Rules Editor** dialog box, complete the following substeps:
 1. In the **Rules name** box, type **Invoice Validation**.
 2. In the **Rule type** list, select **Routing rule**.
 3. Under **Statements**, complete the following substeps to include a statement **for Check for Errors in GL Coding**:
 1. Click **New**.
 2. In the **Statement Editor** dialog box, complete the following substeps:
 1. In the **Statement name** box, type **Check for Errors in GL Coding**.
 2. Under **Conditions**, click the **Add** icon.
 3. In the **Add Condition** dialog box, complete the following substeps:
 1. In the **Constraint by** list, select **Custom property**.
 2. In the **Type** list, select **Normal**.
 3. In the **Field** list, select **AP Detail Valid**.
 4. In the **Operator** list, select **starts with**.
 5. In the **Value** box, type **ERR**.
 6. Click **OK** to close the **Add Condition** dialog box.
 4. Under **Actions**, click **Add** and select **Route to**.

5. In the **Queues** dialog box, complete the following substeps:
 1. In the **Business Process** list, select your workflow process.
 2. Under **Available queues**, select **APO NonPO Invoice GL** or the name of the queue in your process where GL coding is entered and then click **Add**.
 3. Click **OK** until you return to the **Workflow Designer** task pane.

Add the eForm and iScripts to queues

After you add the server validation script and create the routing rules used in the eForm workflow process, you must modify the properties of the workflow queues and add the eForm to user work queues.

Assign the AP invoice form to the following queues:

- APO Invoice Entry
- APO NonPO Invoice GL
- APO NonPO Invoice Approval
- APO PO Invoice Matching

Apply the AP_Validate_Server.js script as an inbound action to the following queues:

- APO Validate/Route Invoice
- APO NonPO Invoice Validation
- APO Invoice Upload

Apply Invoice Entry Validation routing rule as a within queue action to the following queues:

- APO Validate/Route Invoice
- GL Coding Validation

Configure validation within the eForm

AP Invoice eForm includes both client-side and server-side methods of data validation.

Client-side validation allows your users to verify their data in the eForm user interface instantly. The user also receives feedback as he or she types values into fields, or upon clicking the “Validate” button on the form. The user interface error messages and field-flagging enables users to correct errors or omissions before saving or routing the eForm.

Server-side validation completes eForm verification with the AP_Validate_Server.js script, when run as a queue action. This validation process processes all AP Invoice eForm documents that pass through the queue, regardless of whether a user views or modifies document in the user interface. The validation script creates error codes, which you can use when creating routing rules.

To configure validation, review and complete the following tasks, as necessary.

Enable validation for specific roles and queues

Client-side validation for specific roles

Client-side validation takes place within queues attributed to a role, such as Invoice Entry. The first step towards allowing any validation to occur in the user interface is to enable the role or roles. Complete the following steps.

1. Navigate to **[drive:]inserver6\etc\ap** and open **AP_Skin.xml** with a text editor.
2. Locate the `<roles>` node.
3. For any queue that requires header-level, client-side validation, in the corresponding `<role>` element, set the `header` attribute to **enabled**. To run detail-level validation, enable the corresponding `detail` attribute. In this example, to enable client-side validation in a queue called APO Invoice Entry, you enable the Invoice Entry role.

```
<role name="Invoice Entry" header="enabled" detail="enabled">
  <queue invoicetype="nonpo" changetabs="true">APO Invoice Entry</queue>
</role>
```

Server-side validation for specific queues

Server-side validation occurs within a queue that includes the AP_Validate_Server.js script as an action.

Configure the duplicate invoice check

The duplicate invoice check validates a new invoice against other invoices in ImageNow to determine if it is a duplicate.

Client action: The eForm checks for duplicate invoices after the user provides values for the fields used to determine the uniqueness of an invoice. For example, the eForm could search for duplicate invoices using the values of the Invoice Number and Vendor ID fields. It provides the error message “A duplicate invoice exists in the system. To resolve the conflict, review the current invoice and make any necessary changes.”

There are two forms of duplicate invoice check available.

- The original **duplicate invoice check** method validates the Invoice Number and Vendor Number values against all other invoices in the system.
- The **advanced duplicate invoice** check method allows you to specify an ImageNow view, the specific eForm fields to examine, the number of values that indicate a duplicate invoice, and a tolerance level for those values.

If you enable both forms of duplicate invoice check, AP Invoice eForm defaults to the original validation method.

Duplicate invoice check

To configure the original duplicate invoice check validation, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Config.xml** with a text editor.
2. In the `<dupcheck>` and `<dupcheck_vs1>` elements, set the `enabled` attribute to `true`.
3. The default fields for the **Invoice Number** and **Vendor ID** fields are `tab` (field2) and `f3` (field3). To specify alternate locations for these values in your specific eForm solution, choose from the following values.

- | | |
|-----------------------------------|--------------------------------------|
| • <code>[folder]or[field1]</code> | • <code>[f5]or[field5]</code> |
| • <code>[tab]or[field2]</code> | • <code>[doctype]</code> |
| • <code>[f3]or[field3]</code> | • <code>[drawer]</code> |
| • <code>[f4]or[field4]</code> | • <code>{any custom property}</code> |
- For example, `{Invoice Number}`

Advanced duplicate invoice check

To configure the advanced duplicate invoice check validation, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Config.xml** with a text editor.
2. In the `<dupcheck>` set the `enabled` attribute to `true`.
3. In the `<statement>` element, complete the following substeps.
 - To enable the advanced duplicate invoice check, set `enabled` attribute to `true`.
 - To specify a custom view to match against literals, set the `view` attribute to the name of the view. The default view is All Documents.
 - To set the number of values that must match to indicate a duplicate invoice, set the `match` attribute with an integer. The default is 2.
4. Between the `<statement>` element tags, specify which fields you want AP Invoice eForm to check. Specify a number greater than or equal to the number of values you specified within the element, and use the `|` delimiter. Use any of the following fields:

- | | |
|---------------------------------------|-----------------------------|
| • <code>AddlAmt<1 to 8></code> | • <code>LocationCode</code> |
| • <code>CompanyNumHdr</code> | • <code>MiscCharge</code> |
| • <code>FreightAmount</code> | • <code>PONumber</code> |
| • <code>Hdr<1 to 8></code> | • <code>TaxAmount</code> |
| • <code>InvoiceDate</code> | • <code>TotalAmount</code> |
| • <code>InvoiceNumber</code> | • <code>VendorID</code> |
| • <code>InvoiceReferenceNumber</code> | |

5. Optional. To specify a tolerance level with an amount or percent, complete one of the following steps.
- To set a tolerance amount, following the eForm field name, add # and an integer representing the variance amount. For example, to specify a Total Amount field variance of 3 currency units, such as \$3.00, type `TotalAmount # 3`. In this instance, if all other conditions applied, a Total Amount value of \$9.50 would match a Total Amount value of \$12.00, and the eForm would indicate a duplicate invoice. You may specify a tolerance amount with decimals, such as .01 for one US cent.
 - To set a variance percent for matching an eForm field, include % and an integer representing the variance percent. For example, to specify a variance percent of 10%, type `TotalAmount % 10`.

Example: The default settings create a duplicate invoice check that examines the VendorID, Invoice Number, and Total Amount fields in the All Documents view. The Total Amount field includes a range of +/- 5. If the user enters matching values in two or more fields, the invoice check indicates a duplicate.

```
<statement view="All Documents" match="2" enabled="true">VendorID | InvoiceNumber |  
TotalAmount # 5 </statement>
```

Configure header-level and line-level required fields

Required-field validation verifies that every field you mark as required contains a value.

Client action: The eForm flags any blank, required fields with a red box or red highlighting, and provides the error message "Required fields are missing."

Server action: The validation script sends the error key ERR_REQUIRED_FIELDS to the AP Header Valid or AP Detail Valid custom property.

Complete the following client-side and server-side configuration tasks.

Client-side validation

Complete the following steps.

1. In **AP_Skin.xml**, locate the `<fields>` node.
2. For the first field you want to set as required, locate the corresponding `<header>`, `<poline>`, or `<glline>` element. For example, the element for the Business Unit field is:

```
<header label="lblBusinessUnit" field="cboBusinessUnit">
```

3. Set the required and visible attributes to `"true"`, and set the disabled attribute to `"false"`.
4. To set additional fields as required, repeat the previous steps.

Server-side validation

Complete the following steps.

1. In **AP_Validate_Server.xml**, in the `<required_fields>` element, set the `enabled` attribute to `"true"`.
2. To enable the PO, non-PO, or credit memo header fields, set the corresponding `enabled` attribute to `"true"`. For example, `<pohdr enabled="true">`.
3. To require a header-level field, such as CompanyNumHdr, in the `<worksheet>` element, set the `enabled` attribute to `"true"`.

4. To enable the PO or GL detail fields, set the corresponding **enabled** attribute to "true". For example, `<podetail enabled="true">`.
5. To require a PO or GL line-level field, under the `<podetail>` or `<gldetail>` node, in the corresponding `<worksheet>` element, set the **enabled** attribute to "true". For example, `<worksheet enabled="true" field="ItemNumber">`.

Configure GL code validation

In AP Invoice eForm, the GL code fields appear under the GL DISTRIBUTIONS section. Example GL codes include Account, Sub Account, Unit, and Cost Center. In `AP_Skin.xml`, you can configure which of these GL codes to display and how the field displays in the user interface. You can also configure two types of validation.

With GL code validation, the eForm can check user-provided values in GL code fields against available, corresponding values in the GL Codes virtual table. In the client, the eForm can also verify the authorization of the user entering values on a field-by-field basis. You can enable these validation methods together or separately.

Client action: The eForm flags any fields with an invalid or restricted value with a red box or red highlighting. It displays the error message "GL codes are invalid."

Server action: The validation script sends the error key `ERR_GL_CODES_INVALID` to the AP Detail Valid custom property.

To enable GL code validation, review and complete the following tasks, as needed.

- **Configure the GL Codes source values**
- (Optional) **Configure the GL User and GL Code virtual tables with constraints**
- **Enable the GL code validation**

Configure the GL Codes source values

To validate the values of GL codes in the eForm, you must configure the GL Codes virtual table with source numbers. For virtual table information, refer to the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*. We recommend keeping this guide open or available, as this section heavily references the example virtual tables.

In `AP_Skin.xml`, each `<glline>` element represents a GL Code field, and includes a source attribute. This attribute links to the `GLNumber` column of the GL Code virtual table, indicating which GL Codes are valid for the field. To enable validation of each GL code you use in AP Invoice eForm, complete the following steps.

- In your **GL Code** virtual table, verify or configure source numbers in the **GLNumber** column for each row.
- For client-side validation: in **`AP_Skin.xml`**, for each GL code your eForm uses, in the `<glline>` element, specify the **source** attribute with a source number.
- For server-side validation: in **`AP_Validate_Server.xml`**, under `<glcode_validation>`, for each GL code, specify the **source** attribute with the same source number.

For example: In the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*, in the "GL Code" example table, in the `GLNumber` column, note that the source number 1 corresponds to the `GLCode` column values of 100 and 200. In this instance, if you set the source attribute for **lbiGL1** to 1, then the

eForm validates that the user types either 100 or 200 into the first GL Code in the eForm, such as **Account**.

AP_Skin.xml

```
<glline label="lblGL1" showdesc="true" searchable="true" freeform="false" source="1"
line="1" typeaheadchars="2" visible="true" disabled="false" required="true"
width="50px" captionkey="LBL_GLLINE_GL1" descriptionkey="LBL_GLLINE_GL1_DESC" />
```

AP_Validate_Server.xml

```
<worksheet enabled="false" field="GL1" source="1"></worksheet>
```

Configure the GL User and GL Code virtual tables with constraints

Optional. To validate the authorization of a user to provide a specific value in a GL Code, you must configure the GL User and GL Code virtual tables with constraints. This validation occurs only in the client, and does not have a server-side counterpart. Complete the following steps.

1. In your **GL User** virtual table, create a row for every AP Invoice eForm user. Provide the username in the **UserName** column.
2. Specify a pair of constraints for each user, for example **Department_01** and **KCMO**.
3. In your **GL Code** virtual table, to configure which users can access each GL code value, specify the constraint columns for each row.

Note Valid constraints include strings or numbers.

Note To allow all users to access a GL code, use the constraint **ALL** for both columns.

For example, referring to the Constraint columns in the GL Code and GL User, note that user JDOE could use the values 1101 and 1102, while user JJONES could use the value 1103. Each code has a different source, which indicates that users JDOE and JJONES would use the values in different GL Code fields, such as Account vs. Unit.

Enable the GL code validation

To enable the value and (optional) user constraint validation of your GL codes, complete the following steps.

Client-side validation

- In **AP_Skin.xml**, under the **<fields>** node, for each GL code you want to validate in the client, set the **freeform** and **disabled** attributes to **false**, and set **visible** to **true**. For example,

```
<glline label="lblGL1" field="txtGL1" showdesc="true" searchable="true"
freeform="false" source="1" line="1" typeaheadchars="2" visible="true"
disabled="false" required="true" width="50px" captionkey="LBL_GLLINE_GL1"
descriptionkey="LBL_GLLINE_GL1_DESC" />
```

Note The GL code elements include the **label** attribute **lblGL<1 to 24>**.

Server-side validation

For each GL Code you enabled for validation in the previous section, enable validation in **AP_Validate_Server.xml**. Complete the following steps.

1. In **AP_Validate_Server.xml**, in the **<glcode_validation>** element, set the **enabled** attribute to **"true"**.

2. Under the `<glcode_validation>` element, for each GL code you enabled in AP_Skin.xml, enable the corresponding `<worksheet>` element.

Configure GL account validation

GL account validation verifies the data your users enter in the eForm against the corresponding column of the GL Account virtual table. For more information about this virtual table, in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*, refer to the “GL Account” section.

Client action: The eForm flags the GL line and displays the error message “One or more invalid GL Accounts.”

Server action: The validation script sends the error key ERR_GLACCT to the AP Detail Valid custom property.

Client-side validation

For each field on which you want to enable validation, complete the following step.

- In **AP_Skin.xml**, under the `<fields>` node, for each GL account you want to validate, set the **visible** and **required** attributes to **"true"** and set **disabled** to **"false"**. For example,

```
<glline label="lblGLAcct" field="txtGLAcct" line="1" visible="true" maxlength="10"
required="true" disabled="false" width="50px" captionkey="LBL_GLACCT_GLACCT"/>
```

Note The GL account elements include the seven elements between the `label="lblGLBusUnit"` and `label="lblGLAcct6"`.

Server-side validation

1. In **AP_Validate_Server.xml**, enable the `<glaccount_validation>` element.
2. Under the `<glaccount_validation>` node, for each GL account you want to validate, enable the corresponding `<worksheet>` element. For example,

```
<worksheet enabled="true" field="GLAcct"></worksheet>
```

Configure the Invoice Total field validation

AP Invoice eForm allows you to validate the Invoice Total field in PO, non-PO, and credit memo invoices.

PO invoice validation compares the header-level Invoice Total against the line-level Invoice Lines amount total.

Non-PO and **credit memo** validation methods compare the header-level Invoice Total with the GL Distributions amount total.

Configure amount validation and distribution in PO invoices

For PO invoices, AP Invoice eForm validates the header-level Invoice Total amount against the line-level Invoice Lines amount total. To configure this validation, you can choose whether to include Sales Tax, Freight, Misc, and eight other available “additional charges” in the Invoices Lines amount total.

In other words, if you include additional amounts, the eForm verifies:

$$(\text{Invoice Total}) = (\text{Invoice Lines}) + (\text{included additional charges})$$

You can also allow users to distribute additional amounts from the header-level fields into general ledger-level fields, under GL DISTRIBUTIONS.

If using the Perceptive Intelligent Capture Connector and the “run_ic_mapping” element is enabled, then additional functionality is available. For each header-level field, such as include_tax, if enabled and distributed are both set to “true,” the eForm automatically creates a new GL DISTRIBUTIONS section with a single GL line. For more information about validation with Intelligent Capture Connector, refer to [Intelligent Capture Connector value-mapping validation](#) below.

Client action: The eForm flags the **To Be Distributed** amounts with red boxes. It displays the error message “Invoice Amount not fully distributed.”

Server action: The validation script sends the error key ERR_DISTR to the AP Detail Valid custom property.

To include or distribute additional charge fields, complete the following steps, as needed.

Client-side validation

- In **AP_Skin.xml**, under the <po> node, under the <distribution total> node, set the desired additional charge element to true. The default for every node is false.

For example, to have AP Invoice eForm include the Sales Tax and Freight values in the Invoice Lines amount validated against Invoice Total, configure the following elements.

```
<po>
  <polines>true</polines>
  <change_remitto>true</change_remitto>
  <distributiontotal>
    <include_freight>true</include_freight>
    <include_tax>true</include_tax>
    <include_misc>false</include_misc>
    <include_addl_amt1>false</include_addl_amt1>
    <include_addl_amt2>false</include_addl_amt2>
    <include_addl_amt3>false</include_addl_amt3>
    <include_addl_amt4>false</include_addl_amt4>
    <include_addl_amt5>false</include_addl_amt5>
    <include_addl_amt6>false</include_addl_amt6>
    <include_addl_amt7>false</include_addl_amt7>
    <include_addl_amt8>false</include_addl_amt8>
  </distributiontotal>
</po>
```

Client-side distribution

- In **AP_Skin.xml**, under the <fields> node, in the <header> element for the additional charges you want to distribute, set the distributable attributes to "true".

For example, to distribute the Tax Amount field, but not the Freight Amount field, configure the elements as shown in this example.

```
<header label="lblTaxAmount" field="txtTaxAmount" visible="true" align="right"
maxlength="13" distributable="true" captionkey="LBL_SALES_TAX"/>
<header label="lblFreightAmount" field="txtFreightAmount" visible="true"
align="right" maxlength="13" distributable="false" captionkey="LBL_FREIGHT"/>
```

Server-side validation

- In **AP_Validate_Server.xml**, enable the <po_distribution_validation> node.
- Under the <po_distribution_validation> node, for each additional amount you included in AP_Skin.xml, enable the corresponding <include_> element.

Example

```

<po_distribution_validation enabled="true">
  <include_tax enabled="true" distributed="true"/>
  <include_freight enabled="true" distributed="true"/>
  <include_misc enabled="false" distributed="false"/>
  <include_addl_amt1 enabled="false" distributed="false"/>
  <include_addl_amt2 enabled="false" distributed="false"/>
  <include_addl_amt3 enabled="false" distributed="false"/>
  <include_addl_amt4 enabled="false" distributed="false"/>
  <include_addl_amt5 enabled="false" distributed="false"/>
  <include_addl_amt6 enabled="false" distributed="false"/>
  <include_addl_amt7 enabled="false" distributed="false"/>
  <include_addl_amt8 enabled="false" distributed="false"/>
</po_distribution_validation>

```

Configure Invoice Total validation in non-PO invoices or credit memos

For non-PO invoices and credit memos, AP Invoice eForm validates the header-level Invoice Total amount against the line-level GL Distributions amount total. To customize this validation, you can choose whether to include Sales Tax, Freight, Misc, and the other eight available additional charges in the GL Distributions amount total.

In other words, if you include additional amounts, the eForm verifies that:

$$(\text{Invoice Total}) = (\text{GL Distributions}) + (\text{included additional charges})$$

Client action: The eForm flags the **To Be Distributed** amounts with red boxes. It displays the error message “Invoice Amount not fully distributed” or “Distribution percentages do not total to 100%.”

Server action: The validation script sends the error key ERR_DISTR or ERR_PCT_DISTR to the AP Detail Valid custom property.

To include any additional charges, complete the following steps.

Client-side validation

- In **AP_Skin.xml**, under the **<nonpo>** or **<credit>** node, under the **<distribution total>** node, set the desired additional charge element to **true**. The default for every node is false.

For example, to have AP Invoice eForm include the Sales Tax and Freight values in the GL Distributions amount validated against the Invoice Total amount, configure the following elements.

```

<nonpo>
  <distributiontotal>
    <include_freight>true</include_freight>
    <include_tax>true</include_tax>
    <include_misc>false</include_misc>
    <include_addl_amt1>false</include_addl_amt1>
    <include_addl_amt2>false</include_addl_amt2>
    <include_addl_amt3>false</include_addl_amt3>
    <include_addl_amt4>false</include_addl_amt4>
    <include_addl_amt5>false</include_addl_amt5>
    <include_addl_amt6>false</include_addl_amt6>
    <include_addl_amt7>false</include_addl_amt7>
    <include_addl_amt8>false</include_addl_amt8>
  </distributiontotal>
</nonpo>

```

Server-side validation

1. In **AP_Validate_Server.xml**, enable the **<nonpo_distribution_validation>** or **<credit_distribution_validation>** node, as needed.

2. Under the `<nonpo_distribution_validation>` or credit node, for each additional amount you included in AP_Skin.xml, enable the corresponding `<include_>` element. For example,

```
<nonpo_distribution_validation enabled="true">
  <include_tax enabled="true"/>
  <include_freight enabled="true"/>
  <include_misc enabled="false"/>
  <include_addl_amt1 enabled="false"/>
  <include_addl_amt2 enabled="false"/>
  <include_addl_amt3 enabled="false"/>
  <include_addl_amt4 enabled="false"/>
  <include_addl_amt5 enabled="false"/>
  <include_addl_amt6 enabled="false"/>
  <include_addl_amt7 enabled="false"/>
  <include_addl_amt8 enabled="false"/>
</nonpo_distribution_validation>
```

PO/invoice currency validation

If you use the eForm with Intelligent Capture data extraction, the PO/invoice currency validation verifies the PO currency matches the invoice currency. This validation is not configurable. If the PO virtual table includes values in the currency column, then the validation runs. The currency list is disabled in invoice documents. Users should correct a mismatch on the PO level.

Client action: The eForm displays the error message “The purchase order currency does not match the invoice currency.”

Server action: The validation script sends the error key ERR_CURR_MATCH to the AP Header Valid custom property.

VAT validation

For more information on enabling VAT validation, refer to the [Enable VAT amount validation](#) section.

Intelligent Capture Connector value-mapping validation

Server-side validation

You can configure AP_Validate_Server.xml to validate values mapped with the Intelligent Capture Connector. For more information on the connector, refer to the *Perceptive Intelligent Capture Connector Installation Guide*, available in the Customer Portal.

To enable validation for values from the Intelligent Capture Connector, complete the following steps.

1. In **AP_Validate_Server.xml**, enable `<run_ic_mapping>`.
2. Refer to the following sections and enable or configure validation settings as needed.

Lookup validation

If you enable lookups, AP_Validate_Server.xml compares the data captured from the invoice with the data extracted using lookup from the configured data source for AP Invoice eForm.

Example

```
<lookups enabled="true">
  <lookup maxresult="255" name="businessunit"/>
  <lookup maxresult="1" name="vendor"/>
</lookups>
```

```
<lookup maxresult="125" name="po"/>
</lookups>
```

The validation checks for data that is missing or does not match. Any values that Intelligent Capture is unable to capture from the invoice are automatically completed by the lookup data. Any data that does not match is either replaced or an error message displays.

Maxresult is the maximum number of results you want to include in the returned results.

Name is the name of the reference.

Date mask

This element specifies the default date format for the Invoice Date entry. Valid formats are MMDDYYYY, DDMMYYYY, and YYYYMMDD. Slashes are optional. If not specified, the default format is MMDDYYYY.

Example

```
<datemask>MMDDYYYY</datemask>
```

PO line items

This element allows you to enable and disable Intelligent Capture PO line item processing. If set to FALSE, the data source provides the data to populate the AP Invoice eForm line item section. If set to TRUE, Intelligent Capture provides the data.

The default is FALSE.

Example

```
<polineitemprocessing>>false</polineitemprocessing>
```

For more information about virtual tables, refer to the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*.

Replace vendor number

If a mismatch in vendor numbers is found during validation, you can configure AP_Validate_Server.xml to replace the vendor number captured from the invoice with the vendor number extracted using lookup. To enable vendor number replacement, set <forcevendormatch> to true.

Example

```
<forcevendormatch>true</forcevendormatch>
```

If set to false, the vendor number captured from the invoice is not replaced.

Location code

Use this setting to define the source of the Location code, which is provided at scan time. Intelligent Capture does not provide location code. If using a location code, this value must pass to the Intelligent Capture Connector using an index value that the capture profile sets at scan time. By default, Intelligent Capture uses the ImageNow document key F4 (field4). ImageNow 6.6.x and higher to enable the use of a custom property at capture time. The connector references this value to set the related AP Invoice eForm XML data.

Example

```
<locationcode sourcetype="index" sourcename="f4"/>
```

Valid values for sourcetype are index or customproperty.

Configure separator for multiple PO

The Intelligent Capture Connector supports extraction of multiple PO numbers and displays them as a concatenated list with a delimiter. Specify the delimiter under the `<poseparator>` tag.

Example

```
<poseparator>^</poseparator>
```

A ; (semi-colon) is the default delimiter.

Configure caching

Caching enables quick retrieval of previously searched data in AP Invoice eForm. You can schedule caching by running the `AP_Maintenance.js` file at regular intervals using the Windows Scheduler or by configuring caching in the `AP_Config.xml` file. If you choose to cache data by running the scheduler, you should either disable caching in the `AP_Config.xml` file or provide a cache refresh period longer than the period specified in the Windows Scheduler.

The `AP_GetCompanies.js` script gathers caching data from the virtual tables or the associated ERP application. For additional information on the caching functionality, refer to the `AP_GetCompanies.js` description in the table under [\inserver6\script](#).

To configure caching, complete the following steps.

1. Navigate to `[Drive:]inserver6\etc\lap` and open **AP_Config.xml** file.
2. Under the `<Scripts>` tag, in `<AP_GetCompanies>`, provide a value to the `CacheDuration` parameter to configure the cache refresh duration. You can provide any of the following values.
 - Type 0 if you want the cache to refresh continuously.
 - Type a positive value to specify the duration in minutes after which you want the cache to refresh.
 - Type a negative value or special character if you do not want to refresh the cache.

Configure value added tax within the eForm

Incorporating value added tax (VAT) into your AP Invoice eForm solution allows your users to process and validate invoices and credit memos that include VAT amounts, codes and jurisdictions. You can enable VAT amounts to calculate automatically, per item at the line level, based on the VAT jurisdiction and VAT code combination.

To use VAT with AP Invoice eForm, review and complete the following procedures.

Create and enable the VAT codes

For both purchase order and non-purchase order invoices, AP Invoice eForm provides fields for assigning VAT codes for each line item. The VAT code consists of two components: the jurisdiction and the VAT rate code. To configure AP Invoice eForm to accept line-level VAT code assignment, complete the following steps.

Create and update the virtual tables

To create VAT-specific tables and update your existing virtual tables to include the basic VAT-specific columns, complete the following steps. These steps refer to virtual tables, which we detail in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*.

1. Verify or create the **VAT Code** virtual table with **Jurisdiction**, **VATCode** and **VATRate** columns.
2. Verify or update the **Business Unit** virtual table with a **Jurisdiction** column.
3. Optional. Verify or update the **Purchase Order Lines** virtual table with **Jurisdiction** and **VATCode** columns.

Enable the columns

To enable the VAT-specific columns you created in the previous section, complete the following step.

- In **AP_VirtualTable_Updater.xml**, for each **<recordstructure>** and **<column>** element your solution requires, set the **enabled** attribute to **"true"**. The following example illustrates enabling the VAT Code table and its columns.

```
<recordstructure recordtype="VAT_CODE" table="Z_APW_APVAT_Code" enabled="true">
  <column customprop="Z_APW Active" enabled="true"/>
  <column customprop="Z_APW VAT Jurisdiction" enabled="true"/>
  <column customprop="Z_APW VAT Code" enabled="true"/>
  <column customprop="Z_APW VAT Rate" enabled="true"/>
  <column customprop="Z_APW VAT Description" enabled="true"/>
</recordstructure>
```

Enable VAT at the line level

To enable the global use of VAT in the eForm, at the line level, configure **AP_Skin.xml**. Complete the following steps.

1. Navigate to **[drive:]inserver6\etc\ap** and open **AP_Skin.xml** with a text editor.
2. To display the VAT code at the line level, for each of the following elements, set the **visible** attribute to **"true"**.
 - **<poline label="IbIPOLVATCode" field="cboPOLVATCode"/>**
 - **<glline label="IbIGLVATCode" field="cboGLVATCode"/>**
3. Optional. To allow users to view the Jurisdiction code at the line level, in the following elements, set the **visible** attribute to **"true"**.
 - **<poline label="IbIPOLVATJurisdiction" field="txtPOLVATJurisdiction"/>**
 - **<glline label="IbIGLVATJurisdiction" field="txtGLVATJurisdiction"/>**
4. Optional. To allow users to view the VAT amount at the line level, in the following elements, set the **visible** attribute to **"true"**.
 - **<poline label="IbIPOLVATAmount" field="txtPOLVATAmount"/>**
 - **<glline label="IbIGLVATAmount" field="txtGLVATAmount"/>**
5. Save and close **AP_Skin.xml**.

Enable the VAT amount summary

For each distinct VAT code referenced on an invoice, AP Invoice eForm can summarize the total VAT amounts. In the eForm user interface, the VAT Summary section provides a simple, compiled total of the VAT Base and VAT Amount for each VAT Code.

To enable the VAT amount summary logic, and optionally display the VAT Summary section in the eForm, complete the following steps.

Note To enable VAT sum validation, with or without displaying the VAT amount summary in the eForm, refer to the following [Enable VAT amount validation](#) section.

1. Navigate to `[drive:]inserver6\etc\ap` and open **AP_Skin.xml** with a text editor.
2. To enable VAT summation logic in the eForm, under `<vatsummary>`, set `<enable>` to `true`.
3. Optional. To display the VAT Summary section in AP Invoice eForm, set `<showsection>` to `true`.
4. Save and close **AP_Skin.xml**.

Enable VAT amount validation

To enable validation of the line-level VAT Amount sums against the header-level VAT Total amount, complete the following procedures.

Update the Currency virtual table

Due to rounding rate percentages, the sum total of the line-level VAT Amounts and the header-level VAT Total often contain a degree of variation. To specify an acceptable level of variation for your solution, update the Currency Codes virtual table. For more information, in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*, refer to the "Currency" section.

Complete the following step.

- Update the **Currency** virtual table with **VATVarianceAmount** or **VATVariancePercent** columns.
Note If neither column exists, AP Invoice eForm validation expects an exact match between the line-level VAT Amounts and the header-level VAT Total. If you configure both columns, AP Invoice eForm uses the VATVariancePercent column.

Enable the columns

To enable the VATVarianceAmount and VATVariancePercent columns in the Currency Codes table, configure AP_VirtualTable_Updater.xml. Complete the following step.

- In **AP_VirtualTable_Updater.xml**, in the `<recordstructure recordtype="Z_APW_APCurrency">` element, set the `enabled` attribute to `"true"` for the following columns.

```
<column customprop="Z_APW VAT Variance Amount" enabled="true"/>
<column customprop="Z_APW VAT Variance Percent" enabled="true"/>
```

Enable VAT summation and validation

To enable VAT summation and validation in the eForm user interface, configure AP_Skin.xml. Complete the following steps.

1. Navigate to `[drive:]inserver6\etc\ap` and open **AP_Skin.xml** with a text editor.

2. To convert the Tax Amount label to a VAT Total label in the eForm header, in the `<header label="lblTaxAmount">` element, set the `captionkey` attribute to `LBL_VAT_TOTAL`.
3. To enable VAT summation in the eForm, under `<vatsummary>`, set `<enable>` to `true`.
4. To enable VAT validation in the eForm, under `<vatsummary>`, set `<validatesummary>` to `true`.
5. Save and close **AP_Skin.xml**.

Configure server-side VAT validation

With server-side VAT validation, you can compare the header-level VAT Total field against the line-level VAT Amount fields in a workflow validation queue. Complete the following steps.

Note Server-side validation allows you to validate VAT amounts for each document processed, without requiring the user to complete the validation step in the eForm user interface.

1. Navigate to `[drive:]inserver6\etc\ap` and open **AP_Validate_Server.xml** with a text editor.
2. In the `<vatsummary_validation>` element, set the `enabled` attribute to `"true"`.
3. Save and close **AP_Validate_Server.xml**.
4. Optional. In **Workflow Designer**, create a routing rule to route back for VAT validation-specific errors, using the error code **ERR_VAT_TOTAL_MATCH** for the **Value**. For more information on routing rules, refer to the [Create a rule to route back for header error conditions](#) section.

Associate the vendor VAT registration numbers

To associate vendor VAT registration numbers (VAT IDs) with vendors and enable the Vendor VAT ID field, complete the following procedures.

Verify or create the VAT Registration Number (VAT ID) Vendor and Vendor virtual tables

To create VAT-specific tables and update your existing virtual tables to include VAT-required columns, refer to the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide* and complete the following steps.

1. Create the **VAT_ID_VENDOR** virtual table and all required columns. Refer to the "VAT Registration Number (VAT ID) Vendor" section.
2. Optional. To create a default VAT ID for each vendor, update the **VENDOR** virtual table with a VAT ID column. Refer to the "Vendor" section.

Note The user can modify the default value in the eForm by manually keying a new value, or by selecting a value from the VAT Registration Number virtual table using the search feature.

Enable the Vendor VAT ID field

To enable the Vendor VAT ID header-level field, configure **AP_Skin.xml**. Complete the following steps.

1. Navigate to `[drive:]inserver6\etc\ap` and open **AP_Skin.xml** with a text editor.
2. For the following element, set the `visible` attribute to `true`.
`<header label="lblVendorVATID" field="txtVendorVATID"/>`
3. Save and close **AP_Skin.xml**.

Associate the sold-to VAT Registration Numbers

To associate sold-to VAT registration numbers (VAT IDs) with business units and enable the Sold To VAT ID field, complete the following procedures.

Verify or create the VAT Registration Number (VAT ID) Business Unit and Vendor virtual tables

To create VAT-specific tables and update your existing virtual tables to include VAT-required columns, refer to the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide* and complete the following steps.

1. Create the **VAT_ID_BUS_UNIT** virtual table with the required **BusUnit** and **VAT ID** columns. Refer to the "VAT Registration Number (VAT ID) Business Unit" section.
2. Optional. To create a default VAT ID value for each business unit, update the **BUS_UNIT** virtual table with a **VAT ID** column. Refer to the "Business Unit" section.

Note The user can modify the default value in the eForm by manually keying a new value, or by selecting a value from the VAT Registration Number virtual table using the search feature.

Enable VAT at the header level

In the AP_Skin.xml file, you can enable the global use of VAT in your eForm, at the header level.

1. Navigate to **[drive:]inserver6\etc\ap** and open **AP_Skin.xml** with a text editor.
2. For the following element, set the **visible** attribute to **true**.

- `<header label="lblSoldToVATID" field="txtSoldToVATID"/>`

3. Save and close **AP_Skin.xml**.

Enable the VAT Compliance check box

You can customize the AP Invoice eForm to include a check box that signifies that the invoice follows all rules and regulations around the handling of invoices with VAT. To enable this feature, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\ap** and open **AP_Skin.xml** with a text editor.
2. For the following element, set the **visible** attribute to **"true"**.

- `<header label="lblVATCompliant" field="chkVATCompliant"/>`

Note You can set the **required** attribute to **true**, however the user must still select the check box in the eForm.

3. Save and close **AP_Skin.xml**.

Enable the Automatic Tax Calculation check box

With SAP integrations, the Automatic Tax Calculation check box allows SAP to calculate an invoice tax amount rather than using any value provided in the eForm. When selected, SAP calculates the invoice tax separately with its own internal tables of external tax engine.

If you enable the check box in AP Invoice eForm, the eForm selects the check box by default.

Complete the following steps.

1. Navigate to **[drive:]inserver6\etc\ap** and open **AP_Skin.xml** with a text editor.
2. For the following element, set the **visible** attribute to **"true"**.
 - `<header label="lblAutomaticTaxCalc" field="chkAutomaticTaxCalc"/>`
3. Save and close **AP_Skin.xml**.
4. Start **INTool** by accessing a command prompt and changing directories to **inserver6\bin** or **inserver6\bin64**.
5. To commit the changes, enter the following command to run the **AP_Maintenance.js** script.

```
intool --cmd run-iscript --file AP_Maintenance.js
```

Associate AP Invoice eForm with other ERP application

You can configure AP Invoice eForm to connect with other ERP applications, for example SAP. To enable this you must update the configuration in the **AP_Config.xml** file. By default, the virtual table is configured with the eForm.

Configure AP_Config.xml file

To configure **AP_Config.xml** to associate AP Invoice eForm with other ERP applications, complete the following steps.

1. In the **AP_Config.xml** file, under **<configurations>**, add the **<Connector>** tag.
2. Type the value associated to the ERP that is included in the **[drive:]inserver\script\apef\connectors** folder. For example, to connect AP Invoice eForm to SAP, type **SAPConnector** to the **<Connector>** tag, as the **SAPConnector.js** file is available in this folder.

Configure real-time posting in SAP

If your solution uses Perceptive Connect Runtime or Perceptive Connect with Perceptive Connector for SAP Financial Accounting, you can configure AP Invoice eForm to create, park, post, and cancel invoices and Credit Memos directly in SAP.

The SAP connector allows you to make data channels directly between the eForm and SAP.

To begin, create Integration automated system queues (ASQs) in your eForm workflow and then configure channels with the connector. To configure real-time posting in SAP, complete the following steps.

1. In the AP Invoice eForm workflow, create the following Integration ASQ to create, park, post, and cancel invoices in SAP. For additional information on how to create an Integration ASQ, refer to the *Perceptive Connector for SAP Financials Installation and Setup Guide*.
 - To create invoices, create three Integration ASQs, one for each of the following segments.
 - **Integration ASQ for PO.** To accommodate PO-related invoices to be created in SAP and route them to designated queues
 - **Integration ASQ for non-PO.** To accommodate non-PO-related invoices to be created in SAP and route them to designated queues

- **Integration ASQ for Credit Memo.** To accommodate Credit Memos to be created in SAP and route them to designated queues
 - To park invoices, create three Integration ASQs, one for each of the following segments.
 - **Integration ASQ for PO.** To accommodate PO-related invoices to be parked in SAP and route them to designated queues
 - **Integration ASQ for non-PO.** To accommodate non-PO-related invoices to be parked in SAP and route them to designated queues
 - **Integration ASQ for Credit Memo.** To accommodate Credit Memos to be parked in SAP and route them to designated queues
 - To post previously parked invoices in SAP for PO, non-PO, and Credit Memo, create one Integration ASQ.
 - To cancel invoices in SAP for PO, non-PO, and Credit Memo, create one Integration ASQ.
2. Open **Perceptive Connect Runtime Web Console**, create a channel for each Integration ASQ, and specify a name for the channel. For example, to configure a channel to create PO invoices, name the channel as **APEF_CreateInvoice_PO**. For additional information on how to create a channel, refer to the *Perceptive Connector for SAP Financials Installation and Setup Guide*.

Note The steps to create a channel are based on Perceptive Connect Runtime version 1.0.

3. In **Perceptive Connect Runtime Web Console**, to configure a channel, complete the following steps to map the parameters to each Integration ASQ, as required.
1. Navigate to the **[drive]\{path}\Perceptive AP Invoice eForm 12.1.x for SAP\SAPMappingfiles** directory.

Note In the directory path mentioned above, replace x with the current version number. For example, if the current version is 12.1.0, the directory path is **[drive]\{path}\Perceptive AP Invoice eForm 12.1.0 for SAP\SAPMappingfiles**.
 2. Open **APEF_CreateInvoice_PO.xml** and copy the contents to the wizard box in the **Configure the channel** page.
 3. Click **Save**.

Note The XML map associates the invoice number and fiscal year with Field1 and Field2, respectively, by default. To associate them to a different field or custom property, in the respective XML configuration, change the value of the `<in:key>` element appropriately under `<outputs>` tag.

For additional information on how to create Integration ASQ and map the Integration ASQ using Perceptive Connect Runtime Web Console, refer to the *Create an Integration ASQ* and *Create and configure a channel* sections of the *Perceptive Connector for SAP Financials Installation and Setup Guide*.

Configure real-time lookups from SAP

You can configure the AP Invoice eForm to perform live lookups from SAP. This requires back-end integration of AP Invoice eForm with SAP Financials connector using ImageNow Envoy service. After the configuration is complete, SAP Financials connector receives the eForm data and returns the lookup result. To configure the AP Invoice eForm, complete the following steps.

1. In **ImageNow Management Console**, in the left pane, click **Envoy Services** and then click **New**.
2. In the **Envoy Services** dialog box, in the **Definition** page, set the following attributes.

1. In the **Name** box, type `ErpCommonOperationsService` to identify the remote service.
 2. Optional. In the **Description** box, type a description.
 3. In the **URI** box, type the URI for your connector server in the format `http://<Perceptive Connect Runtime server>:<port>/ws/ErpSyncOperations?wsdl`.
 4. In the **Authentication** list, select **None**.
 5. Optional. If you want to enable interceptor logging for the remote service, select the **Enable interceptor logging** check box.
3. Click **Next**.
 4. In the **Operations** page, in the **ErpCommonOperationsService** operation, select all the check boxes.
 5. Click **Finish**.

Configure eForm for data massaging to SAP

AP Invoice eForm supports data massaging to SAP for CreateInvoice and ParkInvoice synchronous operations. To enable data massaging in AP Invoice eForm, complete the following steps.

1. Create two queues, one for Create Invoice and the other for Park Invoice operation.
2. Configure the following settings.
 - Apply the **AP_SAP_CreateInvoice.js** as an inbound action to the queue for Create Invoice operation.
 - Apply the **AP_SAP_ParkInvoice.js** as an inbound action to the queue for Park Invoice operation.
 - From the `[drive:]inserver6\script` directory, open the **AP_Custom_SAP_Invoice_Operation.js** file, and under `customInvoiceDataMassager` function, include you custom code for data massaging.

Customize document key mapping in ImageNow

After you successfully create or park the document, SAP generates an InvoiceDocNumber and FiscalYear. By default, the InvoiceDocNumber and FiscalYear are mapped to field1 and field2 document key, respectively. You can associate different document keys by updating the `AP_SAP_InvoiceOperations.xml` file that is available in the `[drive:]inserver6\etc` directory.

The following code block shows the XML template of `AP_SAP_InvoiceOperations.xml` file.

```
<?xml version='1.0' encoding='UTF-8'?>
<configuration errorqueue="AP Invoice Error" routeforward="true" nextqueue=" "
worksheet="AP Invoice">
  <!-- @REP_VERSION_NUMBER@ -->
  <envoyservice name="ErpCommonOperationsService" username=" " password=" " />
  <createinvoice>
    <outputmapping>
      <parameter name="InvoiceDocNumber" dockey="field1"></parameter>
      <parameter name="FiscalYear" dockey="field2"></parameter>
    </outputmapping>
  </createinvoice>
  <parkinvoice>
    <outputmapping>
      <parameter name="InvoiceDocNumber" dockey="field1"></parameter>
```



```

        <parameter name="FiscalYear" dockey="field2"></parameter>
      </outputmapping>
    </parkinvoice>
  </configuration>

```

To associate a different document key for the `InvoiceDocNumber` parameter, replace `field1` with a different document key for `dockey` in `<parameter name="InvoiceDocNumber" dockey="field1"></parameter>`.

Configure goods receipts within the eForm for SAP

With AP Invoice eForm for SAP, you can enable goods receipts. Goods receipts allow your users to track the inbound movement of items, such as inventory, without requiring information such as payment or authorization. Each goods receipt includes a document ID, year, and item. The following section describes how to enable goods receipts with AP Invoice eForm for SAP.

Create and enable the goods receipt document

For PO invoices, you can configure the eForm to assign goods receipt details for each line item. The goods receipt details contain the ID, year, and item. To configure AP Invoice eForm to accept line-level goods receipt details, complete the following tasks.

Update the virtual table

To create GR details in AP Invoice eForm, add three columns to the Purchase Order Line table. These columns provide a reference to the goods receipt. Complete the following step.

- Update the **PO Line** virtual table with **GRDocument**, **GRFiscalYear**, and **GRItem** columns. For more information, in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide* refer to the "Purchase Order" section.

Update `AP_VirtualTable_Updater.xml`

To enable the columns you created in the previous step, complete the following step.

- In `AP_VirtualTable_Updater.xml`, for each `<recordstructure>` and `<column>` element your solution requires, set the `enabled` attribute to `"true"`. The following example illustrates how you enable the columns in the goods receipt table.

```

<recordstructure recordtype="PO_LINE" table="Z_APW_APPOLine" enabled="false">
  <column customprop="Z_APW Business Unit ID" enabled="true"/>
  <column customprop="Z_APW PO Number" enabled="true"/>
  <column customprop="Z_APW PO Line Number" enabled="true"/>
  <column customprop="Z_APW PO Item Number" enabled="true"/>
  <column customprop="Z_APW PO Item Description" enabled="true"/>
  <column customprop="Z_APW PO Item Quantity" enabled="true"/>
  <column customprop="Z_APW PO Item UOM" enabled="true"/>
  <column customprop="Z_APW PO Item Unit Price" enabled="true"/>
  <column customprop="Z_APW PO Item Extended Price" enabled="true"/>
  <column customprop="Z_APW PO Line Date Closed" enabled="false" format=""/>
  <column customprop="Z_APW PO Line Taxable" enabled="false"/>
  <column customprop="Z_APW VAT Jurisdiction" enabled="false"/>
  <column customprop="Z_APW VAT Code" enabled="false"/>
  <column customprop="Z_APW PO Item GR Document" enabled="true"/>
  <column customprop="Z_APW PO Item GR Fiscal Year" enabled="true"/>
  <column customprop="Z_APW PO Item GR Item" enabled="true"/>

```



```
</recordstructure>
```

Configure AP_Skin.xml

In the AP_Skin.xml file, you can enable the global use of VAT in the eForm at the line level.

1. Navigate to the **[drive:]\\inserver6\\etc\\ap** directory and open **AP_Skin.xml** with a text editor.
2. To display goods receipt details at a line level, for each element, set the **visible** attribute to **"true"**, and modify the **GRFiscalYear** attribute to **"true"** if needed.

- `<poline label="lblGRDocument" field="txtGRDocument" visible="true">`
- `<poline label="lblGRFiscalYear" field="txtGRFiscalYear" visible="false">`
- `<poline label="lblGRItem" field="txtGRItem" visible="true">`

3. Save and close **AP_Skin.xml**.
4. Start **INTool** by accessing a command prompt and changing directories to **\\inserver6\\bin** or **\\inserver6\\bin64**.
5. Enter the following command to run the **AP_Maintenance.js** script and commit the changes.

```
intool --cmd run-iscript --file AP_Maintenance.js
```

Configure GL distribution on PO invoices

You can configure the AP Invoice eForm to distribute unspecified invoice charges. Based on your configuration, you can either add a separate GL Distribution section to include all additional costs that are not associated with header amounts or you can associate each additional cost with a header amount and Add on Cost (AOC) code. The first option works best for applications like SAP. The second option supports applications like Lawson.

For more information about how to associate additional costs with header amounts and AOC codes, refer to the [Configure add on cost \(AOC\) on PO invoices](#) section.

Configure GL distribution of additional costs not associated to header amount

For PO based invoices in ERP applications that do not support header-level distribution logic, you can add GL Lines without making GL Lines distributable. To implement this behavior, complete the following steps.

1. Navigate to **[drive:]\\inserver6\\etc\\ap** and open **AP_Skin.xml** with a text editor.
2. Under **<po>** tag, set the **<gllines>** tag to **true**.
3. In the line `<header label="lblPOInvoiceGLTotalAmt" field="txtPOInvoiceGLTotalAmt" distributable="true" captionkey="LBL_PO_INV_GL_TOTAL_AMT"/>`, set the **<distributable>** tag to **true**.

Notes

- If the **<gllines>** tag is set to **true**, it is recommended that all elements under the **<distributiontotal>** tag is set to **false**. However, if under the **<distributiontotal>** tag value of the elements is set to **true**, it does not affect the logic or functioning of GL distribution.

- In the eForm that is configured for SAP, the `<gllines>` tag is set to `true` and values of all elements under `<distributiontotal>` tag is set to `false` by default.

Configure add on cost (AOC) on PO invoices

The add on cost (AOC) feature allows you to configure the way you categorize and distribute Sales Tax, Freight, Misc. Charge, and other additional amount charges. These charges appear on PO invoices, but are not included in the purchase order. For Lawson users, this configuration also allows you to export AOC codes with distributed amounts, including GL Code or GL Account information, to the MA540 file.

For example, you could assign a default AOC code and accompanying description to your header-level “Misc. Charge” field, such as “HA – Handling.” During PO invoice processing, your user keys an amount into the “Misc. Charge” field. The GL Distributions section automatically populates the default AOC code, description, distribution amount, and any other default GL information you prefer, such as Account number.

At that point, your user could retain the default AOC code for the Misc. Charge value, or select an alternate code from the AOC list. The user can insert and modify additional distribution lines under the AOC code. For example, the user could split a handling charge across multiple departments, cost centers, or accounting units. The AOC feature supports the ability to incorporate both GL Code and GL Account fields in your GL Distributions section.

To configure AOC codes and PO GL distributed-line exports for Lawson, refer to the following sections.

Create and enable the AOC codes

AP Invoice eForm provides the ability to assign an AOC code for each PO GL header-level field amount. In the eForm, the AOC list populates a concatenated AOC code and optional description. The list can import these values from the AOC GL Code table, the AOC GL Account table, or both.

To configure AP Invoice eForm with AOC functionality, complete the following tasks.

Create the AOC virtual tables

To use AOC, create an AOC GL Code table, an AOC GL Account table, or both, depending on your current usage of the GL Code and GL Account virtual tables. If you use both AOC tables, the AOC list under GL Distributions contains each unique AOC Code and its description. If you use both GL Code and GL Account fields, use matching sets of AOC codes and optional descriptions.

The eForm completes field-level validation with the GL Code and GL Account tables. To pass validation, every code or account field used in the AOC tables must also exist in the corresponding GL Code or GL Account table.

Complete the following steps, as necessary for your solution.

- Create the **AOC GL Account** virtual table with **Table Name**, **Active**, **AOC Code**, and any optional columns. For more information, in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*, refer to the “AOC GL Account” section.
- Create the **AOC GL Code** virtual table with **Table Name**, **Active**, and **AOC Code**, and any optional columns. For more information, in the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*, refer to the “AOC GL Code” section.

Update AP_VirtualTable_Updater.xml

To enable the import of the AOC-specific data you created in the previous section, complete the following step.

- In **AP_VirtualTable_Updater.xml**, for each **<recordstructure>** and **<column>** element your solution requires, set the **enabled** attribute to **"true"**. The following example illustrates how to enable the AOC GL Account virtual table and select columns.

```
<recordstructure recordtype="AOC_GL_ACCT" table="Z_APW_APAOCGLAccount "
enabled="true">
  <column customprop="Z_APW Active" enabled="true"/>
  <column customprop="Z_APW AOC Code" enabled="true"/>
  <column customprop="Z_APW AOC Description" enabled="true"/>
  <column customprop="Z_APW Business Unit ID" enabled="true"/>
  <column customprop="Z_APW GL Acctg Unit" enabled="true"/>
  <column customprop="Z_APW GL Account" enabled="true"/>
  <column customprop="Z_APW GL Sub Account" enabled="true"/>
  <column customprop="Z_APW GL Account Description" enabled="true"/>
  <column customprop="Z_APW GL Account 5" enabled="false"/>
  <column customprop="Z_APW GL Account 6" enabled="false"/>
  <column customprop="Z_APW GL Account 7" enabled="false"/>
  <column customprop="Z_APW GL Account 8" enabled="false"/>
</recordstructure>
```

Enable GL distribution with AOC codes in AP_Skin.xml

In the **AP_Skin.xml** file, to enable the distribution of the header-level additional charges and assign an optional default AOC code to each, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Skin.xml** with a text editor.
2. To enable the AOC list for the GL Distributable fields in PO invoices, under **<fields>**, in the **<addl entries label="lblAOCCode">** element, set the **visible** attribute to **"true"**.
3. To configure distribution, complete the following steps.
 1. Under **<fields>**, in the **<header>** element, such as **<header label="lblFreightAmount">**, set the **distributable** attribute to **"true"**.
 2. Optional. Set the **aoc** attribute with a default AOC code from either the AOC GL Code or AOC GL Account virtual table. For example:

```
<header label="lblFreightAmount" field="txtFreightAmount" visible="true"
align="right" maxlength="13" distributable="true" captionkey="LBL_FREIGHT"
aoc="FR"/>
```

Notes

- If the GL Distributions section is visible, the optional columns in the AOC GL Code and AOC GL Account tables, such as business unit ID, automatically populate the fields.
 - Users have the ability to select any AOC code from the list while processing the PO invoice. Select another AOC code to update the values populated in each GL Code or GL Account field. The eForm completes validation using the GL Code and GL Account tables.
4. Save and close **AP_Skin.xml**.
 5. To commit the **AP_Skin.xml** updates, run the **AP_Maintenance.js** script.

Enable multi-line GL distribution exports for Lawson

Lawson customers can export each line-item amount in the GL Distributions section as a separate line to the MA540 file. To enable the export of distributed amounts, complete the following tasks.

Enable PO GL distributions in AP_Config.xml

To enable the export of PO GL distributed lines to Lawson as individual, line-item amounts, configure the AP_Config.xml file. Complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Config.xml** with a text editor.
2. Under **<AP_Invoice_Export>**, set **<Misc_Line>** to **true**.

Note For all nodes under **<ExportSections>**, the **true/false** settings are case-sensitive.

3. Save and close **AP_Config.xml**.

Configure the miscellaneous line export in AP_Export.xml

Configure your Lawson version of the AP_Export.xml file to export distributed amounts and AOC codes. With this functionality, each PO GL distributed amount exports on its own line for the MA540 file. You configure the values that accompany the distributed amount. For example, company number, vendor ID, invoice number, AOC code, and associated GL codes.

Notes

- The order of the **<field>** elements determines the column order in the CSV file.
- The **sequence** attribute is for your reference only: it does not control the column order.
- You may export both header-level amounts, with the **<misc>** node, and distributed amounts, with the **<misc_line>** node.

Complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Export.xml** with a text editor.
2. Under **<misc_line>**, to configure a **<field>** element for every column you require in your CSV file, complete any of the following steps, as needed.
 - To configure a blank column, in the corresponding **<field>** element, do not assign a value to the **worksheet** or **constant** attributes. Verify the **name** attribute is unique within the **<misc_line>** node.
 - To create a column with a constant value, in a **<field>** element, create or modify the attribute **constant="variable"**. For example, you may configure the MA-REC-TYPE column to carry the value **M**, to denote a Lawson M-line.

```
<field name="MA-REC-TYPE" sequence="1" type="alpha" length="1" constant="M"/>
```
 - To create a column that contains the **Workflow Item Creation Date**, set the **constant** attribute **"{{scandate}}"**, and set the **length** attribute to **"10"**. The date exports in MM/DD/YYYY format.
 - To create a column with incrementing integers, set the **constant** attribute to **"{{sequence}}"**, and set the **length** attribute to a minimum of **"2"**, such as for integers 1 to 99. The sequence iterates for each exported line in the **<misc_line>** node, and resets for each PO Invoice exported concurrently.

- To create a column that maps to an eForm value, set the `worksheet` attribute to the eForm field. For a list of available worksheet attributes, refer to the “Worksheet attribute in AP_Export.xml” column in the **User interface labels** table.

```
<field name="MA-VENDOR" sequence="3" type="alpha" length="9"
worksheet="VendorID"/>
```

3. Save and close **AP_Export.xml**.

Display or hide Purchase Order Lines in Invoice Details section

You can display or hide the PO Lines in the AP Invoice eForm by configuring the **AP_Skin.xml**. If you enable PO line matching, you can view PO lines next to related Invoice lines. If you disable PO line matching, searching a PO number displays all open PO lines and marks them as matched. You can manually unmatch them, if required. To display the PO lines, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Skin.xml** with a text editor.
2. Under `<po>` tag, set the `<linematching>` tag value to `true`. To disable PO Line matching set this value to `false`.
3. Run **AP_Maintenance.js**

Additional fields in Purchase Order Lines

You can display the following two boxes under Purchase Order Lines that are not available under Invoice Lines. For SAP, these fields are visible by default.

- **Available Quantity.** This box displays the quantity available for invoicing, that is, the difference between total PO quantity and invoiced quantity. The Available Quantity is calculated from the PO history in SAP.
- **Available Amount.** This box displays the amount available for invoicing. The Available Amount is calculated by applying the following formula.
 - **Quantity x Unit Price/Price Unit**

Configure AP Invoice eForm for a global environment

By default, AP Invoice eForm uses the language of the locale specified at the operating system level of each ImageNow Client computer. For more information on ImageNow and planning for a global environment, refer to the *Language Pack Getting Started Guide*, available on the Perceptive Software website, in the Customer Portal on the Product Documentation tab.

Configure language, date, and currency settings

To override your Windows regional settings, and set the language so that all users see the same language, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Skin.xml** with a text editor.
Note If working in an active-active server environment, navigate to the **[shared path]inserver6\etc\lap** directory.
2. For `<defaultlanguage>`, complete one of the following substeps.

- To set a generic default language in AP Invoice eForm, use one of these two-character language codes.
 - For Dutch, type **nl**.
 - For English, type **en**.
 - For French, type **fr**.
 - For German, type **de**.
 - For Portuguese, type **pt**.
 - For Spanish, type **es**.

In the example below sets the language to English.

```
<defaultlanguage>en</defaultlanguage>
```

- To set a default language based on a specific country, and to display the date, number, percentage and currency format according to that locale, use one of these four-character language codes.
 - Dutch
 - For Belgium, type **nl-BE**.
 - For Netherlands, type **nl-NL**.
 - English
 - For Australia, type **en-AU**.
 - For Canada, type **en-CA**.
 - For Great Britain, type **en-GB**.
 - For India, type **en-IN**.
 - For the United States, type **en-US**.
 - French
 - For Belgium, type **fr-BE**.
 - For France, type **fr-FR**.
 - For Switzerland, type **fr-CH**.
 - German
 - For Germany, type **de-DE**.
 - For Switzerland, type **de-CH**.
 - Portuguese
 - For Brazil, type **pt-BR**.
 - Spanish
 - For Argentina, type **es-AR**.
 - For Mexico, type **es-MX**.
 - For Spain, type **es-ES**.

- For Spanish-Argentina, type **es-AR**, for Spanish-Mexico, type **es-MX** or for Spanish-Spain, type **es-ES**.

In the example below, the language is set to French, and the country is set to Belgium.

```
<defaultlanguage>fr-BE</defaultlanguage>
```

Note For more information on supported languages, with the associated language and country codes, refer to [Supported languages, countries and currencies](#).

3. Save and close **AP_Skin.xml**.

Custom configuration

To make a culture-specific customization to your AP Invoice eForm, complete the following steps.

1. Navigate to **[drive:]inserver6\etc\lap** and open **AP_Custom_Cultures.xml** with a text editor.

Note If working in an active-active server environment, navigate to the **[shared path]inserver6\etc\lap** directory.

2. For the **<culture>** element, configure the following attributes.
 - For the **name** attribute, type a unique name to identify the specific language and country for which you are customizing the form.
 - For the **base** attribute, type the language code or the language code and country code pair from which culture inherits the properties. For example, en or en-US.

Note For more information on language and country codes, refer to [Supported languages, countries and currencies](#).
 - For the **language** attribute, type the language code, such as en.
3. For the **<numberFormat>** element, configure the following attributes.
 - For **groupseparator**, type the character you want to use to separate number groupings, such as comma (,), period (.), space (ns), or apostrophe (').
 - For **decimalseparator**, type the character you want to use to separate the integer part of a number and the decimal part, such as comma (,) or period (.).
 - For **groupsizes**, type a value for the number grouping size, such as 3,2 grouping.
4. For the **<calendar>** element, configure the following attributes.
 - For **separator**, type the character you want to use to separate the day, month, and year values of the date string, such as forward slash (/), hyphen (-), or period(.).
5. For the **<patterns>** element, configure the following attributes.
 - For **shortinput**, type the short date format, without separators, that you want to use to format your dates, such as MMddy.
 - For **longinput**, type the long date format, without separators, that you want to use to format your dates, such as MMddyyyy.
 - For **display**, type the short date format, with separators, that you want to use to display your dates, such as MM/dd/yyyy.
6. For the **<messages>** element, configure the following attributes.

- For **key**, type the predefined property or custom property you want to configure.
- For **caption**, type a literal text replacement for the property.

Note For more information on these attributes, refer to [Appendix B: User interface labels, tooltips, and messages](#).

- For each culture-specific region that you want to customize, repeat the previous steps.
- Save and close **AP_Custom_Cultures.xml**.

Supported languages, countries and currencies

AP Invoice eForm supports the following languages, country-specific languages and currencies:

| Supported Language | Language Code | Supported Country | Country Code | Supported Currency | Currency Code |
|--|---------------|---|--|--|---|
| Dutch | nl | Belgium Netherlands | BE NL | Euro Euro | EUR |
| English English (en) is the default language. | en | Australia Canada Great Britain India Ireland South Africa United States | AU CA GB IN IE ZA US | Australian dollar Canadian dollar British pound Indian rupee Euro South African rand US dollar | AUD CAD GBP INR EUR ZAR USD |
| French | fr | Belgium France Switzerland | BE FR CH | Euro Euro Swiss frank | EUR CHF |
| German | de | Germany Switzerland | DE CH | Euro Swiss frank | EUR CHF |
| Italian | it | Italy Switzerland | IT CH | Euro Swiss frank | EUR CHF |
| Brazilian Portuguese | pt | Brazil | BR | Brazilian reel | BRL |
| Spanish | es | Argentina Columbia Ecuador Mexico Spain | AR CO EC MX ES | Argentinian peso Columbian peso Ecuadorian sucre Mexican peso Euro | ARS COP ECS MXP EUR |

Note Additional country locales may be supported. Contact your Perceptive Software representative for more information.

Additional supported currencies

In addition, AP Invoice eForm supports the following currencies:

| Country | Supported Currency | Currency Code |
|---------|--------------------|---------------|
| Denmark | Danish Krone | DKK |
| Finland | Euro | EUR |
| Sweden | Swedish krona | SEK |

Configuration considerations

Note For specific instructions on configuring your language, refer to the *AP Invoice eForm Installation and Setup Guide*.

When you configure ImageNow in a global environment, configure the following settings:

- Windows regional settings
- Keyboard configuration
- Language Bar

For specific instructions on changing these settings, refer to Windows Help and Support.

Windows regional settings

To display ImageNow data in your ImageNow Client or WebNow browser according to your locale, configure Windows regional settings to the language and locale you are running, such as Spanish in Spain or Spanish in Mexico. The formatting guidelines for each region vary. Refer to Microsoft Windows help for more information.

Keyboard configuration

You can easily define a list of languages to be available for your own use, by adding or removing input languages in the Regional and Language Options in the Microsoft Windows Control Panel. For example, two users in the same department can configure a different input language on their respective devices. One user can use an English (United States) keyboard layout and a German (Germany) keyboard layout, while the other user can use English (United Kingdom) keyboard layout and a German (Swiss German) keyboard layout. This allows each user to insert or display text in both languages.

Language Bar

After you customize your keyboard layout, use the Microsoft Windows Language Bar located on your desktop or Taskbar to switch between the input languages you have added. You can move the Language Bar anywhere on your desktop or minimize it to the Taskbar.

When you change your language of choice using the Language Bar, the selected language applies only to the currently active software program. For example, if your default language is English (United States), you open Microsoft Word, and you then change your language to German (Germany), the setting only

applies to Microsoft Word. All other programs you subsequently open use English (United States). Always verify that you are using the correct keyboard layout and language of choice when switching between programs.

Appendix A: Add a custom currency example

The following steps show you how to add support for an additional currency to the AP Invoice eForm. For more information on virtual tables, refer to the *Perceptive AP Invoice eForm Virtual Tables Configuration Guide*. In the example below, the AP Invoice eForm includes the Venezuelan Bolívar (VEB).

1. Add a record to the **VENDOR** virtual table with Venezuela's country code, **VE**.
2. Add a record to the **CURRENCY** virtual table for the **Venezuelan Bolívar**.

| | A | B | C | D | E | F | |
|---|------------------|------------------|---------------------|---------------------|-----------------|---------------|--|
| 1 | TableName | BusUnitID | CurrencyCode | CurrencyName | PayGroup | Active | |
| 2 | CURRENCY | 1234 | VEB | Venezuelan Bolívar | 7000 | A | |

3. Add a record to the **COUNTRYCURRENCY** virtual table, tying Venezuela's country code, **VE**, to the Venezuelan Bolívar currency, **VEB**.

| | A | C | B | D | E | |
|---|------------------|---------------------|--------------------|-------------------|---------------|--|
| 1 | TableName | CurrencyCode | CountryCode | LocaleCode | Active | |
| 2 | COUNTRYCURRENCY | VEB | VE | es-VE | Y | |

4. In a text editor, open the **AP_Custom_Cultures.xml** file, and complete the following substeps:
 1. Add a new culture section, with formatting details, for the currency you just added.
 2. In the new culture section, specify the group separator and the decimal separator.

```
<cultures>
  <culture name="es-VE" base="es" language="es">
    <numberFormat groupSeparator="." decimalSeparator=",">
    </numberFormat>
  </culture>
</cultures>
```

Note The culture name in the XML file must match the LOCALECODE in the COUNTRYCURRENCY virtual table.

3. Save and close the **AP_Custom_Cultures.xml** file.
5. Start **INTool** by accessing a command prompt and changing directories to **\inserver6\bin**.

Note To use the 64-bit version of INTTool, change the directory to **\inserver6\bin64**.
6. Enter the following command to run the AP_Maintenance.js script and commit the changes.


```
intool --cmd run-iscript --file AP_Maintenance.js
```
7. Complete the following substeps to verify the currency formatting:
 1. Open the AP Invoice eForm.
 2. Select the vendor you added in the previous steps and enter a value in the **Invoice Amount** field.
 3. Verify the value follows the correct currency formatting for the Venezuelan Bolívar.

Appendix B: User interface labels, tooltips, and messages

User interface labels

The following table lists the available captionkeys and user interface captions for customization in the AP_Custom_Cultures.xml file.

In the case of eForm fields, such as Vendor Name, the table also lists the corresponding worksheet attribute for the AP_Export.xml file. Some fields, such as Business Unit, can export more than one value, such as the business unit number (CompanyNumHdr) and the business unit name (CompanyNameHdr). You can map one or both fields in the AP_Export.xml file independently.

SAP labels: The default UI captions for some fields in the SAP version vary from the defaults provided for other versions. The table below notes these differences. You may still configure these captions with the AP_Custom_Cultures.xml file.

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_LOADING | Loading form | |
| LBL_BUSINESS_INFO | Business Information | |
| LBL_INV_INFO | Invoice Information | |
| LBL_GL_DIST | GL Distributions | |
| LBL_INV_LINES | Invoice Lines | |
| LBL_BUS_UNIT | Business Unit SAP: Company Name | CompanyNumHdr CompanyNameHdr |
| LBL_LOC | Location | LocationCode LocationName |
| LBL_PO_NUM | PO Number | PONumber Note Only for Credit Invoice |
| LBL_PO_AMT | PO Amount | POAmount POCurrency |
| LBL_VEND_NAME | Vendor Name | VendorName |
| LBL_VEND_ID | Vendor Number | VendorID |
| LBL_REMIT_TO | Remit To | RemitTo |
| LBL_VEND_ADDR | Vendor Number | VendorAddress |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_VEND_LOC | Vendor Location | VendorLocation VendorLocationName |
| LBL_VEND_SHORT_NAME | Short Name | VendorShortName |
| LBL_VEND_PAY_TERMS | Payment Terms | VendorPaymentTerms |
| LBL_VENDOR_VAT | VAT | VendorVAT |
| LBL_VEND_FIELD_1 | Field 1 | VendorField1 |
| LBL_VEND_FIELD_2 | Field 2 | VendorField2 |
| LBL_INV_NUM | Invoice Number SAP: Reference | InvoiceNumber |
| LBL_INV_DATE | Invoice Date SAP: Document Date | InvoiceDate |
| LBL_INV_DUE_DATE | Invoice Due Date SAP: Due Date | InvoiceDueDate |
| LBL_INV_AMT | Invoice Amount SAP: Amount | TotalAmount |
| LBL_INV_REF_NUM | Invoice Ref Num | InvoiceReferenceNumber |
| LBL_CREDIT_REASON | Credit Reason | CreditMemoReason |
| LBL_SALES_TAX | Sales Tax Note If utilizing VAT with your eForm, use LBL_VAT_TOTAL rather than this caption key. | TaxAmount |
| LBL_VAT_TOTAL | Value added tax (VAT) Note If utilizing VAT with your eForm solution, use this caption key rather than LBL_SALES_TAX. | TaxAmount |
| LBL_FREIGHT | Freight SAP: Unplanned Delivery Cost | FreightAmount |
| LBL_MISC_CHARGE | Misc. Charge | MiscCharge |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_PAY_IMMEDIATELY | Pay Immediately | PayImmediately |
| LBL_ADDL_AMT_1 | Addl Amt 1 | AddlAmt1 |
| LBL_ADDL_AMT_2 | Addl Amt 2 | AddlAmt2 |
| LBL_ADDL_AMT_3 | Addl Amt 3 | AddlAmt3 |
| LBL_ADDL_AMT_4 | Addl Amt 4 | AddlAmt4 |
| LBL_ADDL_AMT_5 | Addl Amt 5 | AddlAmt5 |
| LBL_ADDL_AMT_6 | Addl Amt 6 | AddlAmt6 |
| LBL_ADDL_AMT_7 | Addl Amt 7 | AddlAmt7 |
| LBL_ADDL_AMT_8 | Addl Amt 8 | AddlAmt8 |
| LBL_PO_INV_GL_TOTAL_AMT | GL Total | POInvoiceGLTotalAmt |
| LBL_SUT_CODE | SUT Code | SUTCode |
| LBL_SUT_APPLY | SUT Apply | SUTApplyCode SUTApplyCodeName |
| LBL_UUT_CODE | UUT Code | UUTCode |
| LBL_TAX_EXEMPT | Tax Exempt | TaxExempt |
| LBL_CURRENCY | Currency | Currency CurrencyName |
| LBL_PAY_GROUP | Pay Group | PayGroup |
| LBL_SPECIAL_HANDLING | Special Handling | SpecialHandling |
| LBL_PAYMENT_COMMENTS | Payment Comments SAP: Document Header Text | Comments |
| LBL_HDR_1 | Hdr1 | Hdr1 |
| LBL_HDR_2 | Hdr2 | Hdr2 |
| LBL_HDR_3 | Hdr3 | Hdr3 |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_HDR_4 | Hdr4 | Hdr4 |
| LBL_HDR_5 | Hdr5 | Hdr5 |
| LBL_HDR_6 | Hdr6 | Hdr6 |
| LBL_HDR_7 | Hdr7 | Hdr7 |
| LBL_HDR_8 | Hdr8 | Hdr8 |
| LBL_HDR_9 | Hdr9 | Hdr9 |
| LBL_HDR_10 | Hdr10 | Hdr10 |
| LBL_POLINE_MATCH_SELECT_ALL | Select All | POLineMatchSelectAll |
| LBL_POLINE_MATCH | Match | UpdateHost |
| LBL_POLINE_TAXABLE_SELECT_ALL | Select All | POLineTaxableSelectAll |
| LBL_POLINE_TAXABLE | Taxable | POLineTaxable |
| LBL_POLINE_POLINE_NUM | Line # SAP: PO Line Number | LineNumber |
| LBL_PO_NUM | PO Number | LinePONumber PO_ LinePONumber |
| LBL_POLINE_ITEM_NUM | Item # | ItemNumber PO_ ItemNumber |
| LBL_POLINE_DESCRIPTION | Description | ItemDescription PO_ ItemDescription |
| LBL_POLINE_QUANTITY | Quantity | Quantity PO_ Quantity |
| LBL_POLINE_OPEN_QUANTITY | Available Quantity | PO_OpenQuantity |
| LBL_POLINE_UOM | UOM | UOM PO_UOM |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|--|
| LBL_POLINE_UNITPRICE | Unit Price | UnitPrice PO_UnitPrice |
| LBL_POLINE_PRICEUNIT | Price Unit | PriceUnit PO_PriceUnit |
| LBL_POLINE_EXT_AMT | Extended Amount | ExtendedAmount PO_ExtendedAmount |
| LBL_POLINE_OPEN_AMT | Available Amount | PO_OpenAmount |
| LBL_POLINE_GR_DOCUMENT | GR Document | GRDocument PO_GRDocument |
| LBL_POLINE_GR_FISCAL_YEAR | GR Fiscal Year | GRFiscalYear PO_GRFiscalYear |
| LBL_POLINE_GR_ITEM | GR Item | GRItem PO_GRItem |
| LBL_POLINE_PO_1 | PO1 | PO1 PO_PO1 |
| LBL_POLINE_PO_2 | PO2 | PO2 PO_PO2 |
| LBL_POLINE_PO_3 | PO3 | PO3 PO_PO3 |
| LBL_POLINE_PO_4 | PO4 | PO4 PO_PO4 |
| LBL_POLINE_PO_5 | PO5 | PO5 PO_PO5 |
| LBL_POLINE_PO_6 | PO6 | PO6 PO_PO6 |
| LBL_POLINE_PO_7 | PO7 | PO7 PO_PO7 |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_POLINE_PO_8 | PO8 | PO8 PO_PO8 |
| LBL_POLINE_PO_9 | PO9 | PO9 PO_PO9 |
| LBL_POLINE_PO_10 | PO10 | PO10 PO_PO10 |
| LBL_POLINE_NUM | Line # | PO_LineNumber |
| LBL_GLLINE_TAXABLE_SELECT_ALL | Select All | GLLineTaxableSelectAll |
| LBL_GLLINE_TAXABLE | Taxable | |
| LBL_GLLINE_PCT | Pct | LinePct |
| LBL_GLLINE_AMT | Amount | LineAmount |
| LBL_GLLINE_GL1 | Account SAP: G/L Account | GL1 |
| LBL_GLLINE_GL1_DESC | Account Description SAP: G/L Account Description | GL1Desc |
| LBL_GLLINE_GL2 | Unit SAP: Cost Center | GL2 |
| LBL_GLLINE_GL2_DESC | Unit Description SAP: Cost Center Description | GL2Desc |
| LBL_GLLINE_GL3 | Sub Unit SAP: Profit Center | GL3 |
| LBL_GLLINE_GL3_DESC | Sub Unit Description SAP: Profit Center Description | GL3Desc |
| LBL_GLLINE_GL4 | Sub Acct SAP: WBS | GL4 |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_GLLINE_GL4_DESC | Sub Acct Description SAP: WBS Description | GL4Desc |
| LBL_GLLINE_GL5 | Activity | GL5 |
| LBL_GLLINE_GL5_DESC | Activity Description | GL5Desc |
| LBL_GLLINE_GL6 | GL6 | GL6 |
| LBL_GLLINE_GL6_DESC | Activity Description | GL6Desc |
| LBL_GLLINE_GL7 | GL7 | GL7 |
| LBL_GLLINE_GL7_DESC | Activity Description | GL7Desc |
| LBL_GLLINE_GL8 | GL8 | GL8 |
| LBL_GLLINE_GL8_DESC | Activity Description | GL8Desc |
| LBL_GLLINE_GL9 | GL9 | GL9 |
| LBL_GLLINE_GL9_DESC | Activity Description | GL9Desc |
| LBL_GLLINE_GL10 | GL10 | GL10 |
| LBL_GLLINE_GL10_DESC | Activity Description | GL10Desc |
| LBL_GLLINE_GL11 | GL11 | GL11 |
| LBL_GLLINE_GL11_DESC | Activity Description | GL11Desc |
| LBL_GLLINE_GL12 | GL12 | GL12 |
| LBL_GLLINE_GL12_DESC | Activity Description | GLDesc |
| LBL_GLLINE_GL13 | GL13 | GL13 |
| LBL_GLLINE_GL13_DESC | Activity Description | GL13Desc |
| LBL_GLLINE_GL14 | GL14 | GL14 |
| LBL_GLLINE_GL14_DESC | Activity Description | GL14Desc |
| LBL_GLLINE_GL15 | GL15 | GL15 |
| LBL_GLLINE_GL15_DESC | Activity Description | GL15Desc |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_GLLINE_GL16 | GL16 | GL16 |
| LBL_GLLINE_GL16_DESC | Activity Description | GL16Desc |
| LBL_GLLINE_GL17 | GL17 | GL17 |
| LBL_GLLINE_GL17_DESC | Activity Description | GL17Desc |
| LBL_GLLINE_GL18 | GL18 | GL18 |
| LBL_GLLINE_GL18_DESC | Activity Description | GL18Desc |
| LBL_GLLINE_GL19 | GL19 | GL19 |
| LBL_GLLINE_GL19_DESC | Activity Description | GL19Desc |
| LBL_GLLINE_GL20 | GL20 | GL20 |
| LBL_GLLINE_GL20_DESC | Activity Description | GL20Desc |
| LBL_GLLINE_GL21 | GL21 | GL21 |
| LBL_GLLINE_GL21_DESC | Activity Description | GL21Desc |
| LBL_GLLINE_GL22 | GL22 | GL22 |
| LBL_GLLINE_GL22_DESC | Activity Description | GL22Desc |
| LBL_GLLINE_GL23 | GL23 | GL23 |
| LBL_GLLINE_GL23_DESC | Activity Description | GL23Desc |
| LBL_GLLINE_GL24 | GL24 | GL24 |
| LBL_GLLINE_GL24_DESC | Activity Description | GL24Desc |
| LBL_GLLINE_DR_CR_IND | Debit/Credit | GLDrCrInd |
| LBL_DEBIT_INDICATOR | Debit | |
| LBL_CREDIT_INDICATOR | Credit | |
| LBL_MULPO_NUMS | PO Numbers | PONumber |
| LBL_MULPO_SEARCH_FILTER | Filter | |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_EXCLUDE_MATCHED_LINES | Exclude matched lines | |
| LBL_INV_DETAIL | INVOICE DETAILS | |
| LBL_GLACCT_BUS_UNIT | Business Unit SAP: Company Code | CompanyNum |
| LBL_GLACCT_ACCTG_UNIT | Acctg Unit | GLUnit |
| LBL_GLACCT_GLACCT | GL Acct | GLAcct |
| LBL_GLACCT_SUB_ACCT | Sub Account | SubAcct |
| LBL_GLACCT_ACCT_DESC | Account Description | GLAcctDesc |
| LBL_GLACCT_5 | GL Acct 5 | GLAcct5 |
| LBL_GLACCT_6 | GL Acct 6 | GLAcct6 |
| LBL_TOTAL_DIST | Total Distributed | |
| LBL_TO_BE_DIST | To Be Distributed | |
| LBL_VALIDATE | Validate | |
| LBL_PO_DATE | PO Date | |
| LBL_PO_DATE_MATCHED | Date Matched | |
| LBL_PO_DATE_CLOSED | Date Closed | |
| LBL_SEARCH_TITLE | Search | |
| LBL_POLINES_TITLE | PO Lines | |
| LBL_CREDIT_MEMO | Credit Memo # | InvoiceNumber |
| LBL_CREDIT_DATE | Credit Date | InvoiceDate |
| LBL_CREDIT_AMT | Credit Amount | CreditAmount |
| LBL_VEND_ID | Vendor Number | VendorID |
| LBL_VEND_NAME | Vendor Name | VendorName |
| LBL_SEARCH_VENDOR_ADDR | Address | |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|---|
| LBL_REMIT_TO | Remit To | RemitTo |
| LBL_MIN_CHAR | (minimum 3 characters) | |
| LBL_OK | OK | |
| LBL_CANCEL | Cancel | |
| LBL_LINES_ADD | Add a line | |
| LBL_LINES_DELETE | Delete this line | |
| LBL_INVTYPE_PO | PO | |
| LBL_INVTYPE_NON_PO | Non-PO | |
| LBL_INVTYPE_CREDIT | Credit | |
| LBL_ADDL_ENTRY_DESC | Description | AOCCode |
| LBL_ADDL_ENTRY_AMT | Extended amount | AOCDescription |
| LBL_POLINE_VAT_JURISDICTION | Jurisdiction | PO_VATJurisdiction |
| LBL_POLINE_VAT_CODE | VAT Code SAP: Tax Code | POLVATRate POLVATCode |
| LBL_POLINE_VAT_AMOUNT | VAT Amount SAP: Tax Amount | POLVATAmount |
| LBL_POLINE_PO_VAT_JURISDICTION | Jurisdiction | POLVATJurisdiction |
| LBL_POLINE_PO_VAT_CODE | VAT Code | PO_VATCode PO_VATRate |
| LBL_GLLINE_VAT_JURISDICTION | Jurisdiction | GLVATJurisdiction |
| LBL_GLLINE_VAT_CODE | VAT Code SAP: Tax Code | GLVATCode GLVATRate |
| LBL_GLLINE_VAT_AMOUNT | VAT Amount | GLVATAmount |
| LBL_SEARCH_VENDOR_VAT | VAT | |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption Caption attribute in AP_Custom_Cultures.xml | Worksheet attribute in AP_Export.xml Element in AP_Invoice.xml |
|--|---|--|
| LBL_SEARCH_VENDOR_FIELD1 | Field 1 | |
| LBL_SEARCH_VENDOR_FIELD2 | Field 2 | |
| LBL_VAT_SUMMARY | VAT SUMMARY | |
| LBL_VAT_SUMMARY_CODE | VAT Code | VATSummaryCode |
| LBL_VAT_SUMMARY_BASE | VAT Base | VATSummaryBase |
| LBL_VAT_SUMMARY_AMOUNT | VAT Amount | VATSummaryAmount |
| LBL_VAT_SUMMARY_TOTAL | VAT Sum | VATSummaryTotal |
| LBL_VAT_VEND_ID | VAT Vendor ID | |
| LBL_SOLD_TO_VAT_ID | Sold-To VAT ID | SoldToVATID |
| LBL_VAT_COMPLIANT | VAT Compliant | VATCompliant |
| LBL_TOTALS | TOTAL DISTRIBUTION | |
| LBL_VAT_TOTAL | VAT Total SAP: Tax Amount | |
| LBL_INV_POSTING_DATE | Invoice Posting Date SAP: SAP Entry Date | |
| LBL_AUTO_TAX_CALC | Automatic Tax Calculation | |

Tooltips

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface caption |
|--|--|
| TOOLTIP_DATE_FORMAT | Please enter date in {datemask1} or {datemask2} format. Note AP Invoice eForm replaces {datemask1} and {datemask2} with the appropriate date format, as determined by AP_Custom_Cultures.xml. For example, "Please enter date in MMDDYYYY or MMDDYY format." |
| TOOLTIP_CLOSE | Close |
| TOOLTIP_IMG_PO_LINES_DIALOG | View PO Lines |
| TOOLTIP_IMG_GL_ACCT_SEARCH_WINDOW | Look Up Account |
| TOOLTIP_IMG_PO_SEARCH_WINDOW | Look Up PO Number |
| TOOLTIP_IMG_VENDOR_SEARCH_WINDOW | Look Up Vendor |
| TOOLTIP_IMG_VENDOR_REMIT_TO_WINDOW | Look Up Remote To |
| TOOLTIP_IMG_GL_SEARCH_WIND | Look Up Account |
| TOOLTIP_IMG_VENDOR_VAT_ID_SEARCH_WINDOW | Look Up Vendor VAT ID |
| TOOLTIP_IMG_SOLD_TO_VAT_ID_SEARCH_WINDOW | Look Up Sold-To VAT ID |
| TOOLTIP_IMG_MULPO_EDIT_WINDOW | + or – PO Numbers |
| TOOLTIP_IMG_REFRESH_PO_LINES | Refresh PO Lines |

Error and confirmation messages

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface captions |
|--|---|
| ERR_GEN | Error running eForm. Please check the log files for more information. |
| ERR_NONE | No errors. |
| ERR_DISTR | Invoice Amount not fully distributed. |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface captions |
|---|---|
| ERR_PCT_DISTR | Distribution percentages do not total to 100%. |
| ERR_GLACCT | One or more invalid GL Accounts. |
| ERR_GLACCT_MISSING | Enter GL Distribution Entries. |
| ERR_EXTAMT | Line Item amounts do not total Extended Amounts. Please check distribution. |
| ERR_PREVIOUSLY_EXPORTED | This invoice was previously processed. |
| ERR_REQUIRED_FIELDS | Required fields are missing. |
| ERR_GL_CODES_INVALID | GL codes are invalid. |
| ERR_SEARCH_LIMIT | incomplete |
| ERR_NO_MATCH | No match found. |
| ERR_VENDOR_NOT_FOUND | Vendor not found. |
| ERR_DUP_CHECK | The duplicate invoice detection process requires configuration. Contact your system administrator. |
| ERR_DUP_INVOICE | A duplicate invoice exists in the system. To resolve the conflict, review the current invoice and make any necessary changes. |
| ERR_PO_CLOSED | This PO is closed. |
| ERR_PO_NUM_NOT_FOUND | PO number not found. |
| ERR_CURR_MATCH | The purchase order currency does not match the invoice currency. |
| ERR_CONFIG | Configuration error: {value1} permission = '{value2}'. Changing to '{value3}'. |
| ERR_PO_GL_DISTR | GL distributions not fully distributed |
| ERR_DATE_FORMAT | Enter a date in {datemask1} or {datemask2} format. Note AP Invoice eForm replaces {datemask1} and {datemask2} with the appropriate date format, as determined by AP_Custom_Cultures.xml. For example, "Please enter date in MMDDYYYY or MMDDYY format." |

| Captionkey attribute in AP_Skin.xml Key attribute in AP_Custom_Cultures.xml | Default English user interface captions |
|---|--|
| ERR_CURRENCY_FORMAT | Enter an amount in ###{decimalmask1}## format. Note AP Invoice eForm replaces ###{decimalmask1}## with the appropriate decimal format, as determined by AP_Custom_Cultures.xml. |
| ERR_DECIMAL_FORMAT | Enter a decimal in ###{decimalmask1}## format. Note AP Invoice eForm replaces ###{decimalmask1}## with the appropriate decimal format, as determined by AP_Custom_Cultures.xml. |
| ERR_PERCENT_FORMAT | Enter a percentage in ###{decimalmask1}## format. Note AP Invoice eForm replaces ###{decimalmask1}## with the appropriate decimal format, as determined by AP_Custom_Cultures.xml. |
| ERR_VAT_TOTAL_MATCH | The header-level Value Added Tax does not match the line-level Value Added Tax. |
| ERR_CURR_MATCH | The purchase order currency does not match the invoice currency. |
| ERR_SOLD_TO_VAT_ID_NOT_FOUND | No VAT ID found for the selected business unit. Enter a VAT ID or contact a system administrator to request that a VAT ID be added for this business unit. Note \n\n places two new lines between the first and second sentences. |
| ERR_VENDOR_VAT_ID_NOT_FOUND | No VAT ID found for the selected vendor. Enter a VAT ID or contact a system administrator to request that a VAT ID be added for this vendor. Note \n\n places two new lines between the first and second sentences. |
| ERR_INVALID_PO | The vendor for this PO Number does not match the vendor for the previously selected PO Number. Enter a valid PO Number or remove selected PO Numbers and try again. |
| ERR_VENDOR_DIFFERENT | Invalid PO Number for the selected vendor Enter a valid PO Number for the current vendor or remove selected PO Numbers and try again |
| ERR_INV_AMT_NEGATIVE | Invalid debit amount Enter a positive amount or use credit |
| CONFIRM_PO_NUMBER_CHANGE | The form will replace all existing lines related to the PO number. Do you want to change the PO number? |

| Captionkey attribute in AP_Skin.xml Default English user interface captions | |
|--|---|
| Key attribute in AP_Custom_Cultures.xml | |
| CONFIRM_PO_NUMBER_CHANGE_ POLINEMATCHING | The form will clear all captured invoice data. Do you want to change the PO number? |
| MESSAGE_PO_NUMBER_CLEAR | To clear all PO and GL lines, click the Clear Form Data button above. |
| TEXT_CRITERIA_VENDOR_SEARCH | Enter vendor name. |
| TEXT_CRITERIA_GL_ACCT_SEARCH | Enter account description. |
| TEXT_CRITERIA_PO_SEARCH | Enter vendor ID. |
| TEXT_MATCH | match |
| TEXT_MATCHES | matches |

Appendix C: Document types and custom properties

The AP Invoice eForm installation process creates two document types, Invoice and Credit Memo. It also creates the custom properties required by each document type. The following tables describe the custom properties associated with the document types.

Invoice

| Custom Property Name | Data Type | Description |
|-----------------------|-----------|---|
| Company | String | The business unit for the invoice |
| Vendor ID | String | The unique identification number for the vendor associated with the invoice |
| Vendor Name | String | The name of the vendor associated with the invoice |
| Invoice Number | String | The unique number associated with the invoice |
| Invoice Date | Date | The invoice issue date |
| Invoice Due Date | Date | The invoice due date |
| Invoice Amount | Number | The invoice total amount |
| Invoice Tax Amount | Number | The invoice total tax amount |
| Pay Immediately | Flag | A flag that indicates whether the invoice is processed immediately |
| PO Number | String | The unique purchase order number associated with the invoice |
| PO Amount | Number | The purchase order amount associated with the invoice |
| PO Variance Amount | Number | The amount, in dollars, for variance exceptions |
| PO Variance Factor | Number | The amount, in percentages, for variance exceptions |
| AP Header Valid | String | The header error codes used for exception handling |
| AP Detail Valid | String | The detail error codes used for exception handling |
| AP Custom Valid | String | The custom error codes used for exception handling |
| Invoice Export Status | String | The invoice export status |

Credit Memo

| Custom Property Name | Data Type | Description |
|--------------------------|-----------|---|
| Company | String | The invoice business unit |
| Vendor ID | String | The unique identification number for the vendor associated with the invoice |
| Vendor Name | String | The name of the vendor associated with the invoice |
| Credit Memo Number | String | The unique number associated with the credit memo |
| Credit Date | Date | The credit memo creation date |
| Credit Amount | Number | The total amount of the credit memo |
| Credit Tax Amount | Number | The total amount of taxes of the credit memo |
| Pay Immediately | Flag | Flag that indicates whether the invoice is processed immediately |
| PO Number | String | The unique purchase order number associated with the invoice |
| PO Amount | Number | The purchase order amount associated with the invoice |
| PO Variance Amount | Number | The amount, in dollars, for variance exceptions |
| PO Variance Factor | Number | The amount, in percentages, for variance exceptions |
| AP Header Valid | String | The header error codes used for exception handling |
| AP Detail Valid | String | The detail error codes used for exception handling |
| AP Custom Valid | String | The custom error codes used for exception handling |
| Invoice Export Status | String | The invoice export status |
| Invoice Reference Number | String | The invoice number that the credit memo refers to |
| Credit Reason | String | The reason for the credit memo issuance |

Appendix D: AP Invoice eForm file directories

The following table details the directories of all of the AP Invoice eForm files that the system installs when you run the AP Invoice eForm installation wizard.

\inserver6\etc\ap

| Installed Form File | Description |
|-----------------------------|---|
| AP_Config.xml | This XML file stores the business application name. Leave the <virtualtable> attribute value as true unless this is a custom form implementation. Valid entries include Lawson, PeopleSoft, and Great Plains. The selected business application appears in this XML file in the <host> element. You can use the eForm for virtually any business application that receives uploaded invoices. To install the eForm for any other business application, choose one of the existing available business application options that best fits the scenario. |
| AP_Custom_Cultures.xml | This XML file contains the configuration information used for global customization in your AP Invoice eForm. |
| AP_Export.xml | This XML file contains the configuration information used when you are exporting data from ImageNow to your business application. |
| AP_Skin.xml | This file is the main configuration file for the invoice form. |
| AP_Validate_Server.xml | This XML file contains the data-mapping configuration between your form and the custom properties and document keys in ImageNow. Use this file to configure which fields are required user entries in the form. |
| AP_VirtualTable_Updater.xml | This XML file contains the configuration information used for importing data from your business application, via CSV data files, into the virtual tables. |

\inserver6\temp\ap

If your ImageNow Server is not on the C:\ drive, you use a non-Windows platform, or you have an active-active server environment, then you must configure the directory paths in the **AP_VirtualTable_Updater.xml** and **AP_Export.xml** files. The tables below outline the directories as they appear by default in **AP_VirtualTable_Updater.xml**.

Default paths:

| Default Directory | Description | File | Attribute |
|------------------------------|---|-----------------------------|-------------|
| C:\inserver6\temp\ap\archive | The location where the AP_VirtualTable_Updater.js script sends the CSV data files after processing. | AP_VirtualTable_Updater.xml | archivepath |
| C:\inserver6\temp\ap\error | The location where the AP_VirtualTable_Updater.js script sends the CSV files if it encounters errors. | AP_VirtualTable_Updater.xml | errorpath |

| Default Directory | Description | File | Attribute |
|-----------------------------|---|-----------------------------|-----------|
| C:\inserver6\temp\ap\export | The location where the AP_VirtualTable_Updater.js script sends the exported data files for upload into your business application. | AP_Export.xml | outputdir |
| C:\inserver6\temp\ap\import | The location from which the AP_VirtualTable_Updater.js script imports CSV files. | AP_VirtualTable_Updater.xml | inputpath |

\inserver6\script

| Installed Form File | Description |
|------------------------------|---|
| AP_Custom_Invoice_Export.js | The form uses this script to massage export data. This script should contain all custom functions you need to export valid data. |
| AP_Custom_Validate_Server.js | The form uses this script when you write custom validation logic. |
| AP_DupCheck.js | The form uses this script to execute duplicate invoice logic. The configuration section for duplicate check is located in the AP_Config.xml file. |
| AP_GetGLAcctCode.js | The form uses this script to retrieve GL account codes. |
| AP_GetCompanies.js | <p>The form uses this script to retrieve Business Unit, SUT, Currency, Location, Special Handling codes, and other information.</p> <p>To improve performance while loading the eForm, the eForm caches the drop-down values that the AP_GetCompanies.js script gathers from the virtual tables or associated ERP application. The script saves the cached file in [Drive:]\inserver6\form\<APEF form directory>\GetCompaniesCache.js on the server. Each time the ImageNow or WebNow client opens the form, this cache file is sent to the client along with other presentation files like AP_SkinCache.js.</p> <p>The script runs every time the eForm loads and whenever the cache is stale. The following configurable parameter determines when the cached values become stale.</p> <p>The cache duration is defined in CacheDuration parameter in <AP_GetCompanies> tag under <scripts> tag of the AP_Config.xml file. By default, the script caches these values for 60 minutes. You can adjust this time as necessary.</p> <p>Important If you are testing AP_VirtualTable_Updater.js and do not see the changes (new values) reflected in the AP Invoice eForm, run AP_Maintenance.js script.</p> |
| AP_GetData.js | The form uses this script to retrieve PO information related to the Credit invoice type. |
| AP_GetData_Custom.js | The form uses this script to get your custom data, if any. |

| Installed Form File | Description |
|--------------------------------|---|
| AP_GetGLAcctCodes.js | The form uses this script to retrieve GL Codes. |
| AP_GetGLCodeLists.js | The form uses this script to retrieve a GL Code list from the GL Codes table. |
| AP_GetGLCodeUserConstraints.js | The form uses this script to retrieve the GL User constraints per GL Codes. |
| AP_GetPO.js | The form uses this script to retrieve Purchase Order information given a vendor ID or vendor name. |
| AP_GetPOLines.js | The form uses this script to retrieve Purchase Order information. |
| AP_GetVendorLoc.js | The form uses this script to retrieve vendor location information. |
| AP_GetVendors.js | The form uses this script to retrieve Vendor Information for the vendor list in the Vendor Search dialog box. |
| AP_Invoice_Export.js | ImageNow uses this script to export XML data from ImageNow into the appropriate format for the related business application. |
| AP_Maintenance.js | The form uses this INTool script to complete client side caching and other maintenance tasks associated with performance. We recommend that you schedule this script to every minute. |
| AP_ReindexAndCPMapping.js | Use this script in ImageNow workflow to index form data and set form data into custom properties based on the AP_Validate_server.xml file configuration. |
| AP_ValidateGLAcctCodes.js | Use this script to validate GL Account code entries. The script is executed when the user clicks the VALIDATE button on the GL Entry portion of the form. |
| AP_Validate_Server.js | Use this script in ImageNow workflow to validate form values, retrieve data, and populate custom properties or document key values. Apply the script as an in-bound action. |
| AP_ValidateGLCodes.js | The form uses this script to validate GL code entries. The script runs when the user clicks the VALIDATE button on the GL Entry portion of the form. |
| AP_VirtualTableInstaller.js | The installer uses this script to install the virtual tables. |
| AP_VirtualTable_Purge.js | INTool calls this whenever the Purge routine needs to be run against the virtual table data. |
| AP_VirtualTable_Updater.js | Use this script to update your virtual tables with the business application data from the CSV files. |

\inserver6\form\[build folder]

The build folder name appears in a format similar to 2000000003_00006T3XEMH3. You can locate the following files in the \inserver6\form\[build folder] directory.

Note You may also see the build folder path as \inserver6\worksheet\[build folder].

| Installed Form File | Description |
|-------------------------------|---|
| AP.xsl | This file is the presentation file for the AP Invoice eForm. Do not modify this file. Instead, use the AP_Skin.xml file and the WorksheetStylesheet.css file to alter the form format and presentation. |
| AP_CustomValidation_Client.js | This file contains any custom logic that you might add as form event handlers. For example, when the user tabs away from an eForm field, you might want to add some additional processing logic. The logic, implemented as a JavaScript function, would be placed in this file. |
| AP_Worksheet_Scripts.js | ImageNow uses this script within the form to provide search dialogs for looking up general ledger account codes and looking up vendors. The form uses this script to apply the configurations contained within the AP_Skin.xml file to the form display and to validate form data. |
| AP_SkinCache.js | This local cache file loads inline logic to the invoice form when the form opens. |
| AP_Skin.xml | This file contains a cached copy of the configuration settings AP.xsl uses. |
| <customerlogo>.jpg | This is the customer logo image file used in the invoice form. This file name must match the customerlogo entry in the AP_Skin.xml file. |
| globalize.js | This file contains all the generic globalization functions used by the AP Invoice eForm. This file also contains the default values for the en-US language setting for when the system does not detect a valid language. Do not modify this file. |
| globalize_culture_all.js | This file contains the culture information for all supported cultures. Do not modify this file. |
| globalize_culture_custom.js | This file contains customization configurations to cultures or newly defined cultures. Do not modify this file. |
| WorksheetStylesheet.css | This is the cascading style sheet file used for the presentation of the AP Invoice eForm. Use this file to modify the styles used in your form implementation. |

\inserver6\form\data_definition

The following XML files are located in the \inserver6\form\data_definition directory.

Note You may also see this folder path as \inserver6\worksheet\data_definition.

| Installed Form File | Description |
|---------------------|--|
| AP_Invoice.xml | <p>This file is the data definition file for the AP Invoice eForm and typically should not need modification. The only modification that is allowed is the default setting for the invoice type.</p> <p>The supported invoice types are PO, Non-PO, and Credit Memo in any of the following variations.</p> <ul style="list-style-type: none"> For PO - "po" For Non-PO - "no-po", "non-po", "nopo", "nonpo", "n-po", "npo" For Credit Memo - "credit", "credit memo", "credit-memo", "cm" <p>The values for the file types are not case sensitive.</p> |

\inserver6\log

Log files associated with the invoice form installation and configuration are stored in the \inserver6\log directory.

| Installed Form File | Description |
|--|--|
| AP_GetCompanies_<current date>.log | This log file is created after you open the form. |
| AP_GetVendors_<current date>.log | This log file is created after you run a vendor search in the form. |
| AP_VirtualTable_Installer_<current date>.log | This log file is created after you run the installer. The file details the success or failure of the virtual table creation during installation. |
| AP_VirtualTable_Updater_<current date>.log | This log file is created after you run the AP_VirtualTable_Updater.js script. The log file details the success or failure of the virtual table updates between ImageNow and the CSV data files the customer places in the path specified in the input path variable in the ap_virtualtable_updater.xml file. |

Appendix E: Custom logic

Global variables

These variables are available for use in the AP_CustomValidation_Client.js for custom scripting.

| Variable | Description |
|-------------|--|
| gInitialTab | The value of the document's invoice type. For example, PO, non-PO, or credit memo. |
| gUserName | The value of the user currently viewing the eForm. |
| gDocID | The value of the document ID. |
| gExportDate | The date on which AP_Invoice_Export.js exported the document. |
| gDocType | The document's type. |
| gFolder | The value of the document's folder index key. |
| gTab | The value of the document's tab index key. |
| gField1 | The value of the document's Field1 document property. |
| gField2 | The value of the document's Field2 document property. |
| gField3 | The value of the document's Field3 document property. |
| gField4 | The value of the document's Field4 document property. |
| gField5 | The value of the document's Field5 document property. |
| gDrawer | The value of the document's drawer. |
| gQueue | The value of the queue where the document exists at the time the script runs. |

Custom functions

You can use the following functions to customize your AP Invoice eForm.

| Function | Description |
|--------------------------------|--|
| custom_headerPermission | Set this function to true to enable header customization. |
| custom_detailPermission | Set this function to true to enable detail header customization. |
| custom_glDetailPermission | Set this function to true to enable GL detail header customization. |
| custom_glDetailPOPermission | Set this function to true to enable GL detail PO invoice header customization. |
| custom_glDetailNonPOPermission | Set this function to true to enable GL detail Non-PO invoice header customization. |

Add custom business logic to the form

Use the following methods, called user exits, to add your own business logic to AP Invoice eForm without causing the solution to fail.

- Adding JavaScript event handlers to form field events such as onclick and onblur.
- Calling a server-side iScript from the form to complete database lookups or validation.
- Supplementing the validation script provided with AP Invoice eForm (the inbound iScript that runs after an invoice is routed forward).

The following sections explain these user exits.

JavaScript event handlers

The file AP_CustomValidation_Client.js has user exit points where you can add custom logic to handle various events that occur in the AP Invoice eForm. The following custom scripting events are available:

- When the user opens the form (body onload event).
- When the user changes a field's value in a form. You can perform event handling, such as onclick or onblur.
- When you use custom code to handle the following JavaScript events.

| Event | Description |
|------------|---|
| onblur | Occurs when an element loses focus. |
| onclick | Occurs when the user clicks an object. |
| onfocus | Occurs when an element has focus. |
| onkeydown | Occurs when a keyboard key is pressed. |
| onkeypress | Occurs when a keyboard key is pressed or held down. |

| Event | Description |
|-------------|--|
| onkeyup | Occurs when a keyboard key is released. |
| onmouseover | Occurs when the mouse button is moved over an element. |
| onmouseout | Occurs when the mouse button is moved off an element. |
| onmouseup | Occurs when the mouse button is released. |

- When the user clicks the Validate button, either before the validate event or after the validate event, the following actions occur:
 1. The before validate event runs. You can insert custom logic before out-of-the box validation code runs.
 2. Standard out-of-the-box validation code runs.
 3. The after validate event runs. You can insert custom logic after the out-of-the box validation code runs.
- When the user adds a row to the eForm.
- When the user closes the form (body onunload event).

Call a server-side iScript

You can use the iScript dbcall method to call your custom iScript. For example, you can call your own iScript file with the dbcall method when an event such as button click occurs in a form field. A generic button is available for this purpose. For more information on using the dbcall method, refer to the "Form iScript attributes and parameters" topic in *ImageNow Administrator Help*.

An iScript named AP_GetData_Custom.js provides the basic mechanism for exchanging data between the form and your external data sources.

The following example shows how you might modify the AP_GetData_Custom.js file.

```
function main ()
{
    debug = new iScriptDebug("USE SCRIPT FILE NAME", LOG_TO_FILE,
        DEBUG_LEVEL);

    debug.showINowInfo("INFO");

    try
    {
        if( ! CONFIG_VERIFIED )
        {
            var errorStr = "Configuration not verified. Please verify \n" +
                "the defines in the *** Configuration *** section at the\n" +
                "top \n" +
                "of this script and set CONFIG_VERIFIED to true.\n" +
                "Aborting.\n\n";
            debug.log("CRITICAL", errorStr);
            INprintf(errorStr);

            setOutputParams( new Array( "customData.errorMessage = '" +
```

```
        "AP_GetData_Custom.js(): Configuration not verified.
        " + ";" ) );
        return;
    }

    var param = getInputParams();

    if (param.length>0)
    {
        var arg1 = trim(param[0]);
        debug.log("INFO","Input Argument 1: %s\n", arg1);
    }

    //custom code goes here
    var rtnJson = "customData.success = true";

    debug.log("DEBUG", "Returning: %s\n", rtnJson);
    setOutputParams( new Array( rtnJson ) );
```

Enhance the validation iScript

You can use an inbound script to route an item forward to the next queue by writing an iScript file and then calling that file from the AP_Validate_Server.js file. You can also insert the custom script directly in the AP_Validate_Server.js file. The AP_Validate_Server.js file calls your iScript file and then performs that event. The AP_Custom_Validate_Server.js file is available for you to write your custom code. It is called by AP_Validate_Server.js to run your validation.

The following example shows how you might modify the AP_Custom_Validate_Server.js file.

```
function custom_validation(wsXML)
{
    debug.log("INFO", "\n");

    debug.log("INFO", "Custom Validation:\n");

    if (wsXML==null)
    {
        debug.log("ERROR", "\twsXML object is null.\n");
        return;
    }

    //insert your custom logic here

    //examples of how to traverse the wsXML object
    try
    {
        debug.log("INFO", "\tInvoice Number: %s\n", wsXML.InvoiceNumber);
        debug.log("INFO", "\tVendor ID: %s\n", wsXML.VendorID);
        //add your custom validation logic here

    }

    catch (e)
    {
        return 'Error: custom_validation()' + e.toString();
    }

    //use next line if you want to dump contents of wsXML object
    //return "Custom Validation Error";
```

```
//use next line to return no error
return "";
}
```

Enhance the export iScript

The following section provides examples that you can use to enhance the export iScript.

Field level sample

In the following example, the field export massager passes the function two parameters, the field name and the field value (by reference).

```
function custom_field_massager(fieldName, &fieldValue)
{
    debug.log("DEBUG", "Entering function custom_field_massager() ...\n");

    debug.log("DEBUG", "custom_massager -- fieldName:[%s], fieldValue:[%s] --\n",
fieldName, fieldValue);

    //IF FIELD IS MA-VENDOR, prepend 0 padding to 10 characters
    if(fieldName == "MA-VENDOR")
    {
        while(fieldValue.length < 10)
        {
            fieldValue = "0"+fieldValue;
        }
    }
    debug.log("DEBUG", "custom_field_massager() ... returning fieldValue:[%s]\n",
fieldValue);
    debug.log("DEBUG", "Exiting function custom_field_massager() ...\n");
}
```

Global level sample

In the following example, you can customize the global export massager to configure an object to represent all of the data you want to export. For more examples, see the AP_Custom_Invoice_Export.js.

```
function custom_export_massager(&exportObj)
{
    debug.log("DEBUG", "Entering function custom_export_massager() ...\n");
    //MODIFY CONTENTS OF THE HEADER DATA
    //EXAMPLE: IF Vendor is '3004' then set Location and Disc-Date to some value
    if(exportObj.header)
    {
        if(exportObj.header['MA-VENDOR'] == "3004")
        {
            exportObj.header['MA-LOCATION'] = "test location";
            exportObj.header['MA-DISC-DATE'] = "12/31/2010";
        }
    }
    debug.log("DEBUG", "Exiting function custom_export_massager() ...\n");
}
```

Appendix F: Reserved characters in XML and forms

We do not recommend using special characters in queue names.

XML reserves some characters as markup delimiters. These reserved characters cannot appear as a literal string in XML character data, such as the text value of an element. Exceptions occur when you use these characters as markup delimiters, in comments, in processing instructions, and in character data (CDATA) sections.

To use a reserved character in text, use an escape sequence. XML provides standard escape sequences, called character entity references. These provide a way to refer to a character that is not universally encodable.

This table lists reserved characters and the replacement entity references.

| Reserved character | Meaning | Entity reference/escape sequence | Comments/What to use when coding a form |
|--------------------|----------------|----------------------------------|--|
| > | Greater than | \$gt; | For compatibility, this character must be escaped using the entity reference or as a character reference when it appears in the string "]]>" in content and when that string is not marking the end of a CDATA section. |
| < | Less than | < | This character should always appear in content as an escape character so that it does not interact with the syntax of the markup. |
| & | Ampersand | & | This character should always appear in content as an escape character so that it does not interact with the syntax of the markup. |
| ' | Apostrophe | ' | You can symbolize the apostrophe or single-quote character (') with this character entity reference when you need to embed a single-quote or apostrophe inside a string that is already single-quoted. Although ' is part of the XML language, it is not defined in HTML. Use ' if passing text to an HTML user agent. |
| " | Quotation mark | " | You can symbolize the double-quote character (") with this character entity reference when you need to embed a double-quote inside a string that is already double-quoted. Note Use \" when writing unparsed data to XML. |
| % | Percent | % | The Notification Services XML vocabulary reserves the percent sign (%) for denoting parameters. Note % is an escape sequence, but not an entity reference defined by XML. |
| \ | Slash | None required | Note Use \\ when writing unparsed data to XML. |

Appendix G: ERP specific values associated to financial terms

AP Invoice eForm sends ERP-specific values to indicate debit or credit transactions and enable or disable automatic tax calculations. Users select the debit or credit value from a list in the eForm. The eForm provides one set of values for SAP and another set of values for all other ERP applications. The following table lists the values.

| Terms | SAP specific indicator | Indicator for other ERP applications |
|---------------------------|----------------------------------|--------------------------------------|
| Debit or Credit | Debit: S Credit: H | Debit: 1 Credit: 0 |
| Automatic tax calculation | Enable: X Disable: <No value> | Enable: True Disable: False |