Perceptive Interact for Microsoft Dynamics AX

Installation and Setup Guide

Version: 2.2.x

Compatible with ImageNow, Version: 6.7.x







Table of Contents

What is Perceptive Interact for Microsoft Dynamics AXAX	4
Required components	4
Software prerequisites	4
Licenses	5
Interact Viewer Installation	5
Conditions for importing the solution	5
Installation and setup	6
Download the required files from the Customer Portal	6
Copy files to the relevant folders	6
Run Perceptive Interact for Microsoft Dynamics AX Server installer	7
Run Perceptive Interact for Microsoft Dynamics AX Client installer	7
Import Perceptive Interact for Microsoft Dynamics AX model	8
Set up user privileges	9
Set up an environment to log in to ImageNow Server	10
Connect to ImageNow Server	11
Copy an existing configuration	11
Export a configuration	11
Import a configuration	12
Troubleshoot	12
Index	13

What is Perceptive Interact for Microsoft Dynamics AX

Perceptive Interact for Microsoft Dynamics AX is a content management solution for users of Microsoft Dynamics AX. This solution enables you to add and manage documents in ImageNow Server by using the Microsoft Dynamics AX user interface.

This document explains how to set up Perceptive Interact for Microsoft Dynamics AX.

Required components

Software prerequisites

Before you set up Perceptive Interact for Microsoft Dynamics AX, you must have the following software installed on the target machine.

- Microsoft Dynamics AX Server, version 2012 R2 CU6 or R2 CU7, R3, R3 CU8
- Microsoft Dynamics AX Client, version 2012 R2 CU6 or R2 CU7, R3, R3 CU8
- ImageNow Server, version 6.7
- ImageNow Client, version 6.7
- Perceptive Integration Server, version 6.7.0.3667 and higher
- Interact Viewer, version 2.0.x

Notes

- Install ImageNow Client on the same machine on which you install Microsoft Dynamics AX Client.
- For information on installing ImageNow Client and ImageNow Server, refer to *ImageNow Server* and Client Installation and Setup Guide for your environment.
- Perceptive Integration Server, version 6.7

Note For information on installing Perceptive Integration Server, refer to *Perceptive Integration Server Installation and Setup Guide*.

- Browser requirement for Interact is IE 10 or higher. Interact also supports the latest version of Chrome, Firefox and other leading browsers.
- Net Framework, version 4 (full version)

Note Do not install the client version.

You must have the following files ready for use.

- iScripts:
 - DAX_Doc_VersionControl.js
 - DAX_SearchFolderByPath.js
- Installers:
 - PerceptiveInteractforMSDynamicsAXSetupServer_2.2.x.xxx.exe
 - PerceptiveInteractforMSDynamicsAXSetupClient_2.2.x.xxx.exe



Based on the Microsoft Dynamics AX version you use, you must have one of the following Perceptive Interact for Microsoft Dynamics AX model ready to be imported into Microsoft Dynamics AX.

- PerceptiveInteractR2CU62.2.x.xxx.axmodel
- PerceptiveInteractR2CU72.2.x.xxx.axmodel
- PerceptiveInteractR32.2.x.xxx.axmodel
- PerceptiveInteractR3CU82.2.x.xxx.axmodel

Licenses

You must have the following licenses.

- ImageNow Server, version 6.7
- ImageNow Client, version 6.7
- Perceptive Interact for Microsoft Dynamics AX, version 2.2

Interact Viewer Installation

To install the Interact Viewer, perform the following steps.

- 1. Download the required files from the Customer portal.
- 2. Unzip the file to a folder with an appropriate name. For example, perceptive.
- 3. Copy the folder to **webapps** folder in Tomcat server, where Integration Server is installed.
- 4. Restart the Tomcat server.

Conditions for importing the solution

You must prepare the system as follows before importing the solution.

- Ensure that the Microsoft Dynamics Server is running.
- Ensure that the Integration Server is running.
- Set up Perceptive Content so that the appropriate folder types, document types, custom properties, workflow queues, and iScripts are available for use by Perceptive Interact for Microsoft Dynamics AX.

Note For information on configuring ImageNow, refer to ImageNow Administrator Help.

- Verify that you have the following permissions to work with the model.
 - Administrative permissions on the local computer
 - Administrator rights in Microsoft Dynamics AX
 - In Microsoft SQL Server
 - Membership in the Securityadmin server role on the SQL Server instance
 - Membership in the db_owner role in the Microsoft Dynamics AX database



Installation and setup

To set up Perceptive Interact for Microsoft Dynamics AX, perform the following procedures.

- 1. Download the required files from the Customer Portal.
- 2. Copy files to the relevant folders.
- 3. Run Perceptive Interact for Microsoft Dynamics AX Server installer.
- 4. Run Perceptive Interact for Microsoft Dynamics AX Client installer.
- 5. Import Perceptive Interact for Microsoft Dynamics AX model.
- 6. Set up user privileges.
- 7. Set up an environment to log in to ImageNow Server.
- 8. Connect to ImageNow Server.

The following sections provide instructions on how to complete each procedure.

Download the required files from the Customer Portal

- Go to the Perceptive Software website at <u>www.perceptivesoftware.com</u> and log in to the Customer Portal.
- 2. In the Product Downloads page, search for all downloadable items for Perceptive Interact for Microsoft Dynamics AX, version 2.2.
- 3. Download the iScripts, installers, and the required model for your environment to a temporary directory on your computer.

Copy files to the relevant folders

- 1. To make the iScripts available to ImageNow Server, copy and paste the following .JS files to the [drive:]\inserver6\script directory.
 - DAX_Doc_VersionControl.js
 - DAX_SearchFolderByPath.js
- 2. Copy and paste the **PerceptiveInteractforMSDynamicsAXSetupServer_2.2.x.xxx.exe** file to the machine that hosts the Application Object Server (AOS).
- 3. Copy and paste the **PerceptiveInteractforMSDynamicsAXSetupClient_2.2.x.xxx.exe** file to the machine that hosts the Microsoft Dynamics AX Client.



Run Perceptive Interact for Microsoft Dynamics AX Server installer

- 1. Run the **PerceptiveInteractforMSDynamicsAXSetupServer_2.2.x.xxx.exe** file on the machine that hosts the AOS.
- 2. In the Perceptive Interact for Microsoft Dynamics AX Server Installation Wizard window, complete the following substeps.
 - 1. In the Welcome to the Perceptive Interact for Microsoft Dynamics AX Server Installation Wizard page, click Next.
 - 2. In the License Agreement page, scroll down to the end of the agreement, select the I accept the terms in the license agreement check box, and then click Next.
 - 3. In the **Destination Folder** page, ensure that the default location is set to **C:\Program** Files\Microsoft Dynamics AX\60\Server\MicrosoftDynamicsAX\bin\.
 - Optional. To set a different location, click Change and then in the Change Current Destination Folder page, set the correct location, and then click OK.
 - 4. Click Next.
 - 5. In the **Ready to Install the Program** page, to begin the installation, click **Install**.
 - 6. After the installation is complete, in the **Installation Wizard Completed** page, click **Finish** to exit the Installation Wizard.

Run Perceptive Interact for Microsoft Dynamics AX Client installer

- 1. Run the **PerceptiveInteractforMSDynamicsAXSetupClient_2.2.x.xxx.exe** file on the machine that hosts Microsoft Dynamics AX Client.
- 2. In the Perceptive Interact for Microsoft Dynamics AX Client Installation Wizard window, complete the following substeps.
 - 1. In the Welcome to the Perceptive Interact for Microsoft Dynamics AX Client Installation Wizard page, click Next.
 - 2. In the License Agreement page, scroll down to the end of the agreement, select the I accept the terms in the license agreement check box, and then click Next.
 - 3. In the **Destination Folder** page, ensure that the default location is set to **C:\Program Files** (x86)\Microsoft Dynamics AX\60\Client\Bin\.
 - Optional. To set a different location, click Change and then in the Change Current Destination Folder page, set the correct location, and then click OK.
 - 4. Click Next.
 - 5. In the **Ready to Install the Program** page, to begin the installation, click **Install**.
 - 6. After the installation is complete, in the **Installation Wizard Completed** page, click **Finish** to exit the Installation Wizard.



Import Perceptive Interact for Microsoft Dynamics AX model

Before importing the model, complete the following steps.

- 1. Close the client connections to the AOS instance that you are working with.
- 2. If more than one server is using the same database, stop all other AOS instances.

To import the model, complete the following steps.

- 1. On the Start menu, click Command Prompt.
- 2. Navigate to the directory for the management utilities. Typically, the location of this directory is %ProgramFiles%\Microsoft Dynamics AX\60\ManagementUtilities.
- 3. At the command prompt, type the import command, and then press ENTER. The import command syntax is axutil import /file:<File name> where <File name> is the absolute path of the file.
- 4. After completion, start the AOS.
- 5. Open Microsoft Dynamics AX Client. A dialog box appears with the message that the new model has been modified and provides options to run the model as required.
- To upgrade the model, in the Microsoft Dynamics AX dialog box, perform one of the following actions.
 - If you are uploading the model for the first time, select **Start the model upgrade checklist**, click **OK**, and then proceed with the instructions that follow.
 - If you uploaded the same model before, select Compile and synchronize and click OK.
- 7. Optional. If you selected the **Compile and synchronize** option, generate Incremental CIL build from X++ after the compilation and database synchronization is complete. To generate Incremental CIL build from X++, complete the following substeps.
 - 1. In Microsoft Dynamics AX Client, open New Development Workspace and right-click AOT.
 - 2. Click **Add-Ins** and then click **Incremental CIL generation from X++**. When the process is complete, proceed with the usual operations.
- 8. Optional. If you receive a database error, to troubleshoot, complete the following steps.
 - 1. Open Microsoft Dynamics AX Client.
 - 2. In the navigation pane, click **System administration**.



- In the System administration area page, under Periodic, under Database, click SQL administration.
- 4. In the SQL administration window, under All tables, select the following tables.
 - INAutoFoldersRecordLog
 - INDataBaseLogSetup
 - INEnvironmentProfile
 - INFolderSetup
 - INFormGroup
 - INImageNowFormSetup
 - INImageNowParameters
 - INRoleFormAccessSetup
 - INTmpCaptureCustomProperties
- 5. In the menu bar, click **Table actions** and then click **Synchronize database**.
- 6. Close all open windows.
- 7. Restart Microsoft Dynamics AX Client.

Set up user privileges

Perceptive Interact for Microsoft Dynamics AX supports both administrative and end-user tasks. To enable a user to perform any task, in Microsoft Dynamics AX, under Information technology cycle, assign one or more of the following duties and respective privileges to a Microsoft Dynamics AX role as applicable.

For information on how to assign a duty or privilege to a role, refer to Microsoft Dynamics AX Help.

- Maintain Interact setup. This enables the user to perform all administrative tasks in Perceptive Interact for Microsoft Dynamics AX. Assign this duty to the Perceptive Interact for Microsoft Dynamics AX administrator.
- Content maintain. This enables the user to add documents by capturing files and maintain the content documents.
- **View content.** This enables the user to view content documents.



The following table lists the functions that are available to the user for each assigned duty.

Task	Maintain Interact setup	Content maintain	View content
Set up an environment for Interact	✓		
Create a form group for Interact	✓		
Configure a form for Interact	✓		
Modify an existing form configuration	✓		
Remove an existing form configuration	√		
Set up form access for a Microsoft Dynamics AX role	√		
Run a batch job to create automatic folders for old records	√		
Capture a file		✓	
View a captured document			✓
Download a captured document			✓

Set up an environment to log in to ImageNow Server

To perform administrative tasks in Interact for Microsoft Dynamics AX, the user must log in to Perceptive Content within Microsoft Dynamics AX. Before logging in, verify that the user is assigned privileges in Management Console. The following steps explain how to set up the Perceptive Content environment.

- 1. In the navigation pane, click Interact administration.
- 2. In the Interact administration area page, under Setup, click Interact parameters.
- 3. In the Interact parameters window, in the left pane, click Environments.
- 4. Under Set up environments to log in to ImageNow Server, click New.
- 5. In the **Environment profile** box, type a name for the environment.
- 6. Optional. In the **Description** box, type a brief description for the environment.
- 7. Under **Setup**, provide the following credentials.
 - In the User name box, type the user name.
 - In the **Password** box, type the password for the user.
 - In the Integration Server URL box, type the Integration Server URL.



- In the Light Viewer URL box, type the Light Viewer URL.
- In the **WebNow URL** box, type the WebNow URL.

Note Ensure that the format for Integration Server URL, Perceptive Light Viewer URL and WebNow URL is http://<host>:<port number>/< folder name as available in the webapps folder in Tomcat server>.

- 8. To verify the credentials and test Perceptive Server connection, click **Test connection**.
- 9. To set this environment profile as a default environment profile during login, in **Interact parameters** window, complete the following substeps.
 - 1. In the left pane, click General.
 - 2. Under General, in the Default environment profile list, select the environment profile.

Connect to ImageNow Server

To connect to ImageNow Server from within Microsoft Dynamics AX, complete the following steps.

- Under Connect to ImageNow Server, under Credentials, in the User name box, type your user name.
- 2. In the **Password** box, type your password.
- 3. Click OK.

Copy an existing configuration

You can copy an existing Perceptive Interact for Microsoft Dynamics AX configuration from one system environment to another. In Microsoft Dynamics AX, to move a configuration to a new environment, you must export and import groups of tables.

Note In the **Interact administration** area page, you can export and import only the settings under **Form groups** and **Interact parameters**. Export or import functionality is not applicable for **Form access setup** or any other settings.

Export a configuration

To export an existing configuration, complete the following steps.

- 1. In the navigation pane, click Interact administration.
- 2. In the Interact administration area page, under Setup, click Export Interact Configuration.
- 3. In the **Export options** window, on the **General** tab, complete the following steps.
 - 1. In the **File name** box, type a folder path and file name.

Note To select an existing file, click the folder icon.

- 2. In the **File type** list, select the type of file.
- 4. Click OK.



Import a configuration

To import an exported configuration, complete the following steps.

- 1. In the **Interact administration** area page, under **Setup**, click **Import Interact Configuration**. A confirmation message box appears before deleting the configuration data.
- 2. Optional. Maintain a backup of the database.
- 3. To continue with import, complete the following substep.
 - 1. To delete configuration data, click Yes.
- 4. In the **Import options** window, on the **General** tab, complete the following substep.
 - 1. In the **File name** box, type a folder path and file name.
 - **Note** To select an existing file path, click the folder icon.
- 5. Click **OK**. A confirmation message box appears before final execution of the import process.
- 6. Click Yes. Infolog window appears displaying the information of the import process.

Note After every successful import, in the **Interact parameters** window, you need to enter the password under **Setup**. If the password is not entered after the import process, automatic folder creation fails.

Troubleshoot

If a functional issue occurs, use the information in this section to aid with troubleshooting.

- Ensure that the format for Integration Server URL, Light Viewer URL and WebNow URL is http://<host>:<port number>/< folder name as available in the webapps folder in Tomcat server>
- Ensure that the format for WebNow URL is http://<host>:<port number>/< folder name as available in the webapps folder in Tomcat server>/
- Ensure that there is no slash (/) at the end of the Integration Server URL, Light Viewer URL.
- Ensure that there is a slash (/) at the end of WebNow URL.
- If you are unable to view the Light Viewer, copy the Light Viewer URL and paste the URL in IE.
- To add or delete a fact box from Forms section available under the Interact parameters section, ensure that you are an authorized system administrator.



Index

Configuration	
export	11
import	12
Files	
copy	6
download	6
ImageNow Server	
environment	10
login	11
Import	
configuration	12
model	8

nstall	
client	7
server	7
nteract for Microsoft Dynamics AX	
client installer	7
conditions	5
download files	6
import model	8
licenses	5
server installer	7
software prerequisites	4
user privileges	9