Brainware Intelligent Capture Visibility

Technical Specifications

Version: 4.0.x

Written by: Documentation Team, R&D

Date: Tuesday, May 17, 2022



Documentation Notice

Information in this document is subject to change without notice. The software described in this document is furnished only under a separate license agreement and may only be used or copied according to the terms of such agreement. It is against the law to copy the software except as specifically allowed in the license agreement. This document or accompanying materials may contain certain information which is confidential information of Hyland Software, Inc. and its affiliates, and which may be subject to the confidentiality provisions agreed to by you.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright law, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Hyland Software, Inc. or one of its affiliates.

Hyland, HXP, OnBase, Alfresco, Nuxeo, and product names are registered and/or unregistered trademarks of Hyland Software, Inc. and its affiliates in the United States and other countries. All other trademarks, service marks, trade names and products of other companies are the property of their respective owners.

© 2023 Hyland Software, Inc. and its affiliates.

The information in this document may contain technology as defined by the Export Administration Regulations (EAR) and could be subject to the Export Control Laws of the U.S. Government including for the EAR and trade and economic sanctions maintained by the Office of Foreign Assets Control as well as the export controls laws of your entity's local jurisdiction. Transfer of such technology by any means to a foreign person, whether in the United States or abroad, could require export licensing or other approval from the U.S. Government and the export authority of your entity's jurisdiction. You are responsible for ensuring that you have any required approvals prior to export.

Table of Contents

About the Brainware Intelligent Capture Visibility Technical Specifications	4
Intelligent Capture Visibility Server	4
Brainware Intelligent Capture Visibility Client	6
Brainware Intelligent Capture Visibility – Network Port Usage	7

About the Brainware Intelligent Capture Visibility Technical Specifications

This document provides the technical specifications for the Brainware Intelligent Capture Visibility product produced by Hyland Software. The technical specifications in this document are specific to a product release. We publish new technical specification for each major release. For the most accurate information, refer to the technical specifications document that matches your version of the product.

The product highlighted in this specification document has unique requirements. It is important to understand what the product is and how it relates, or does not relate, to the other products.

Visibility is the analytical and production reporting product for use with Brainware Intelligent Capture. This product provides the customer with reports of daily and periodic activity as well as detailed metrics on performance of Intelligent Capture. Visibility is available as a 32-bit or 64-bit application.

Visibility requires a minimum amount of memory and disk space. You must meet these requirements to support your implementation. These requirements specifically list the needs of the product and do not include any amount of memory or disk space you require for the operating system, environment, or other software that runs on the same machine.

Some of these technical specifications also provide minimum recommendations that are based on historical customer implementation/performance data. For maximum performance, review your specific environment, network, and platform capabilities and analyze your planned business usage of the system. Your specific system may require additional resources above these recommendations.

This Technical Specification lists third-party product and platform versions to which the respective vendors provide general support at the time of our release. If the support life-cycle for a third-party product or platform version ends during the life of the Hyland product that supported it, you must either update to a supported version or subscribe to extended support from that vendor. Taking this step ensures that your support from Hyland is sufficient across all products.

Note

As part of the sales process, Hyland provides detailed hardware requirements that are specific to your configuration needs, based on volumes, desired throughput, number of users, existing infrastructure, and so on.

Intelligent Capture Visibility Server

Intelligent Capture Visibility Server is a web server required for implementations where the Visibility reporting product is used. In most situations, you can install Visibility on an existing web server. The number of concurrent users/processes and overall demand might require the installation of Visibility on a separate or dedicated server. Review your anticipated needs with Sales Engineering to confirm server requirements.

The following table lists the minimum technical specifications required for the Intelligent Capture Visibility Server, as well as recommendations. Allow for these recommendations if you install Visibility on an existing server.

Specification	Description, Recommendations and Supported Platforms/Versions
Hardware	Use the following specifications if you install Visibility on a separate server.
	Server class - minimum 4 cores
	• 4+ GB RAM
	250+ GB Hard disk
	Note: For optimal performance, we recommend 3.0+ Ghz processors. Slower processor speeds work, but performance and throughput could be impacted.
Operating Systems	We recommend that you upgrade to the latest operating system patch of the following operating system versions.
	Microsoft Windows Server
	Windows Server 2019
	Windows Server 2017
	Windows Server 2016
	Windows Server 2012 R2
	Windows Server 2008
	Windows Server 2008 R2
	Microsoft
	Windows 10 (64 bit)
	Windows 8 (64 bit)
	Windows 7 (64 bit)
	Web Application Server
	 Apache Tomcat 9.0.68 is installed by default

Specification	Description, Recommendations and Supported Platforms/Versions
	Others .NET Framework 2.0 .NET Framework 4.x .NET Framework 3.5
DBMS	We recommend that you upgrade to the latest DBMS patch of the following versions. Note: For performance reasons, it is highly recommended to put the Visibility database on a dedicated server. Microsoft SQL Server SQL Server 2017 SQL Server 2016 SQL Server 2014 SQL Server 2012 SP2 SQL Server 2008 R2 SQL Server 2019 Oracle Oracle 12c Oracle 11g Oracle 10g Oracle 19c

Brainware Intelligent Capture Visibility Client

Brainware Intelligent Capture Visibility Client is a web-based client used for the Visibility reporting application. The following table lists the minimum technical specifications required for this client.

Specification	Description, Recommendations and Supported Platforms/Versions
Hardware	Processor: 1 Core - 2.4 GHz or greater processor.
	Screen Resolution: The required minimum screen resolution is 1024 x 768; however, 1280 x 1024 SVGA is recommended
Web Browsers	Supported Versions:
	Mozilla Firefox versions 26.x, 40.x, 57.0.x, 61.0.x, and 63.0.x
	Google Chrome versions 31.0, 45.0, 62.0.x, 67.0.x, and 70.0.x
	Safari on Mac versions 4.0.x, and 10.1.2.
	Microsoft Edge 41.x, 42.x and Chromium 91.0.x
Other Applications	Plug-Ins or applications for opening Microsoft Word, Microsoft Excel, and PDF format files (as applicable depending on the client reporting requirements)
Accessibility	A 10 Mb/s connection is required. For optimal performance, use a 100 Mb/s connection.
Memory	1 GB of RAM is required in addition to the recommended RAM for the operating system.
Disk Space	No specific additional disk space requirements needed.

Brainware Intelligent Capture Visibility – Network Port Usage

Brainware Intelligent Capture Visibility uses specific network ports as part of the default implementation. If needed, you can modify port assignments. The following table lists the Internet Assigned Number Authority (IANA) for networking protocols. It is possible that your networking group will have changed ports for database traffic to meet your organization's security requirements.

Port	Usage
1433	Microsoft SQL Database

Port	Usage
1521	Oracle Database
45450	Visibility Product
8080	Visibility Product - default for Apache Tomcat Service
443	Visibility Product - Apache Tomcat Service using SSL
8443	Visibility Product - Apache Tomcat Redirect Service using SSL